




# MENTOR

## Product Line-Up

Cross Roller Slide Guide / Cross Roller Slide Table / Motorized Stage /  
Dovetail Stage / Manual Stage / Micrometer Head



A

## **Crossed Roller Slide Guide**




JV1/ JV2/ JV3/ JV4/ JV6/ JV9/ JVNB6/ JVNB9

JVW1/ JVW2/ JVW3/ JVW4

JC1/ JC2/ JC3/ JC4/ JC6/ JC9

# Cross Roller Slide Guide

〈Fig.1〉 Structure of cross roller guide JV type and JVV type



JV type

JVV type

## Structure

MENTOR cross roller guide JV type is a linear guide instrument by assembling cage actively between two-patterned orbiting planes after making V-shaped two-surfaces as an orbiting groove. It is a highly rigid and precise linear motion system of limited type since rollers are arranged orthogonally so it may receive load from various directions. There are various kinds to choose from. It is in a wide range of applications in precision equipments such as OA instruments and peripherals, or in slides such as optical meter, optical stage, and handling equipments.

## Features

Cross roller guide JV type is used by combining roller cage, which is assembled by arranging precision roller orthogonally, with the roller surface of 90 V groove which is manufactured onto its specialized rail. Since double-ranged roller guide is attached horizontally, the load from all directions passing through the axle at a right angle can be received.

### ■ High rigidity

There is no clearance since applying preload is quite simple. Furthermore, the contact length between the roller and the contact plane is long so that high rigidity can be obtained.

### ■ Soft motion

MENTOR cross roller guide JV type is at an orbiting surface of high precision. Plus, the roller with no skew phenomenon and accurate maintenance for its size is assembled into the cage, so that soft rolling motion with low rolling resistance without stick-slips can be acquired.


### ■ Easy to fix

Fixing holes in the orbiting plane are manufactured with counter and tap process. For fixing onto the orbiting plane, thus, there are two methods; the one is to fix it onto the tap of machine and installments. The other is to push the bolt from the machine and equipments and fix it. So there's no limitation to the fixing structure. Since orbiting plane has uniform structure of two-patterned orbiting planes in the inside, fixing structure is quite simple. Therefore, there is no manufacturing error in fixing part and linear motion of high precision can be obtained.

## Accuracy size

Precision of a rail specialized for cross roller guide is classified into highly superior group and precision group according to <Table.1>

<Fig.2>





<Table 1>

Grade of precision	Highly superior group	Precision group
Items	Symbols	
Parallel of rolling surface to the side of B and C	Refer to <Fig.2>	
Permissible deviation in dimensions of height E	$\pm 0.02$	$\pm 0.01$
Pair deviation of height E (Note)	0.01	0.005
Permissible deviation in dimensions of width A	0 -0.2	0 -0.1

Note) Pair deviation of height E is applied to four-patterned rail used for the same surface.

<Fig.3> Length of a race rail and parallel of rolling surface





## Formation of model number

Cross roller guide is organized as model number as follow, '1 set' in the number mentioned above means combination of four-patterned rail and two-patterned cage.

## Basic static load capacity $C_0$

If excessive load is given to JV type when it is stalled or in motion, there occurs permanent transformation between rolling surface and vibrator. Basic static load capacity ( $C_0$ ) is the load when the sum of permanent transformation volume of the rolling surface and vibrator is 0.0001 times more the diameter of the latter (Refer to Load capacity of each direction in B-11). If the sum of permanent transformation volume breaks 0.0001 times of the diameter, its motion will be adversely affected. Static safety factor ( $f_s$ ) to the load should be considered in order to prevent it. (Refer to Static safety factor B-11)


## Basic dynamic load capacity

When each of JV types in the first group is in motion, the load that does not transform its size at the direction where 90% of the first group's rated life span reaches  $L=100\text{km}$  is called basic dynamic load capacity  $C$ , which can be used for calculating life span. (Refer to B-12 rated life span  $L$ )

## Load capacity in each direction

When each of JV types in the first group is in motion, the load that does not transform its size at the direction where 90% of the first group's rated life span reaches  $L=100\text{km}$  is called basic dynamic load capacity  $C$ , which can be used for calculating life span. (Refer to B-12 rated life span  $L$ )

(Fig.4)



$$C = C_L = \left(\frac{Z}{2}\right)^{\frac{3}{4}} \times C_Z, C_T = 2C$$

$$C_O = C_{O_T} = \left(\frac{Z}{2}\right) \times C_{OZ}, C_{OT} = 2C_O$$

[ Remove numbers coming after the decimal point for  $\frac{Z}{2}$  ]

$C_Z$  : Basic dynamic load capacity in the dimension table ( kN )

$C_{OZ}$  : Basic static load capacity in the dimension table ( kN )

$Z$  : The number of vibrator under use (The number within valid load)

## ■ Static safety factor $f_s$

Sudden external force can be created when JV type stops or is in motion due to vibration, impact or maneuvered stall. For this, static safety factor to the applied load needs to be taken into account.

$$f_s = \frac{C_o}{P_c}$$

$f_s$  : Static Safety factor       $C_o$  : Basic static load capacity  
 $P_c$  : Calculated load

Machine for use	Load condition	Lower limit of $f_s$
Standard industrial machine	With vibration or impact	1.0~1.3
	Without vibration or impact	2.0~3.0
Machine tools	With vibration or impact	1.0~1.5
	Without vibration or impact	2.5~7.0

## ■ Rated life span L

The life span of cross roller guide can be calculated with the following formula after basic dynamic load capacity is calculated.

$$L = \left( \frac{f_T}{f_w} \cdot \frac{C}{P_c} \right)^{\frac{10}{3}} \times 100$$

L : Rated life span (km)

(It's the total distance where 90% of the first group can reach without flaking when each of the same JV type in the first group is put in motion under the same condition.)

$C$  : Basic dynamic load capacity (kN)

$P_c$  : Calculated load (kN)

$f_T$  : Temperature factor (Refer to picture 5)

$f_w$  : Load factor (Refer to table 3)

When the length and lap number of stroke is uniform, service life can be figured by using the following formula after rated life span (L) is calculated from the formula mentioned above.

$$L_h = \frac{L \times 10^6}{2 \times l_s \times n_1 \times 60}$$

$L_h$  : Life time (h)

$n_1$  : Lap number per minute


$l_s$  : Length of stroke (mm)

(min<sup>-1</sup>)

## ■ $f_T$ : Temperature factor

When the environment temperature where the direct-acting system is used is over 100°C, temperature factor below should be multiplied considering the possible adverse effect caused by high temperature.

⟨Fig.4⟩



Note) In case that environment temperature is over 100°C, contact MENTOR.

## ■ $f_w$ : Load factor

Shuffling machines is likely to be affected by vibration or impact during drive. While driving high-speed, particularly, it is a lot more difficult to calculate each value precisely. Therefore, if the load applied to the direct-acting system cannot be calculated or the impact of speed vibration is large, the load factor in the table below should be divided into the basic load capacity (C) and (Co).


⟨Table.3⟩

Vibration • Impact	Velocity (V)	$f_w$
Meager	For meager speed $V \leq 0.25 m/s$	1.0~1.2
Small	For low speed $0.25 < V \leq 1.0 m/s$	1.2~1.5
Averager	For average speed $1.0 < V \leq 2.0 m/s$	1.5~2.0
Large	For high speed $V > 2.0 m/s$	2.0~3.5

## Cross roller guide fixing method

When using clearance adjust bolt

⟨Fig.6⟩ Fixing cross roller guide



① Stick rail 2 and 3 to the base and rail 1 to the fixing plane precisely, and then firmly fasten the rail fixing bolt.

② Fasten rail 4 to the table temporarily.

Note) A fixing bolt for rails should be designed to be able to be fastened after being fixed.

③ Locate the base and table according to the ⟨Fig.6⟩ and then, insert the roller cage from the end. In case the cage failed to be inserted due to no clearance, try installing again after moving the rail 4 to the side to adjust bolt.

④ Set the dial gauge according to the ⟨Fig.6⟩. Regulate all adjust bolts uniformly by pushing the table gently on both sides until no vibration can be felt.

⑤ Fix the stopper at the end of a rail.


⑥ Rectify the location of the cage in order to obtain some scale of strokes by moving the table.

⑦ Locate the roller cage in the middle of a rail according to the ⟨Fig.7⟩ (1). Fasten the adjust bolts b, c, and d within the range of a roller uniformly by using a torque wrench until the dial gauge displays some displacement. Note) Displacement of the dial gauge is the preload of the roller cage in the first row.

⑧ Follow the procedure in the aforementioned and fasten the rest of the adjust bolts a and e by moving the table according to the ⟨Fig.7⟩ (2).

Note) When assembling several groups, calculate the fastening torque or slide frictional resistance force for the first group of adjust bolt. Then, from the second group, almost the same preload can be applied when assembled with same fastening torque or slide frictional resistance force of the first group.


⟨Fig.7⟩ Fastening order of adjust bolts



## ■ Examples of clearance adjustment

Please design the adjust bolts in a way to press the same board with roller.

⟨Fig.8⟩ Examples of clearance adjustment



## ■ Preload of cross roller guide

Excess preload is the cause of errors such as denting or shortened service life. When fastening the adjust bolts, checking displacement value of the roller's fixing plane is needed. Permissible preload of the roller cage in the first row is displayed in the dimension table.

## ■ Precision of fixing plane


In order to obtain highly accurate driving precision, precision tolerance such as parallel or straightness of the rail fixing plane is required. The parallel and sectional level of the rail fixing plane is recommended to map with more than the equivalent of the parallel of a rail based on the grinding work (B-10 <Fig.3>). Likewise, the rail should be fixed precisely in the fixing plane.

## ■ Cautions when using

### ■ Length of a rail

Roller cage moves to the same direction as a half of table movement. Given that the length of a cage  $\ell$  and that of stroke  $\ell_s$ , the length of a rail ( $L_k$ ) should be

$$L_k \geq \ell + \frac{\ell_s}{2} \quad \text{in order for a cage not to be overhung the orbiting plane.}$$




### ■ About stopper

Stopper is attached to the sectional side of a rail to prevent the cage from omitting. But the cage's frequent collision with the stopper, for example, due to over strokes creates the stopper's wear and loosening of its fixed screws. It certainly leads to the falling of a cage. Therefore, separate stopper needs to be made externally so that the occurrence of over strokes as well as the collision of a cage can be prevented.

## ■ Component parts



Fixing rails where clearance adjustment is needed should be fixed by using screw holes manufactured in a rail according to <Fig.9>. In this case, bolt holes ( $d_1$ ), and ( $D_1$ ) needs to be manufactured in proportion to adjusted quantity.

<Fig.9>



If specific structure calls for fixing like the <Fig.10>, fixing bolt (S) of this rail should have its own fixing bolt just like the one displayed in the <Table.4>

<Fig.10>




(Unit: mm)

Model No.	B	d	D	H	L1	L2	S	Supported rail
MBT 3	M3X0.5	2.6	5	3	12	5	2.5	MVR 3
MBT 4	M4X0.7	3.5	5.8	4	15	7	3	MVR 4
MBT 6	M5X0.8	4.4	8	5	20	8	4	MVR 6
MBT 9	M6	5.3	8.5	6	30	11	5	MVR 9





A

**JV 1**

크로스 롤러 슬라이드 가이드  
Crossed - Roller Slide Guide



Specification Model	스토로크 Stroke	주 요 치 수							
		조합지수 Combination Dimension			장착치수				
		B	H	Lo	n x P	G	I	F	S
JV 1 - 20 - 5	12	8.5	4	20	1 x 10	5	3.8	1.8	M2 x 0.4
JV 1 - 30 - 7				30	2 x 10				
JV 1 - 40 - 10				40	3 x 10				
JV 1 - 50 - 13				50	4 x 10				
JV 1 - 60 - 16				60	5 x 10				
JV 1 - 70 - 19				70	6 x 10				
JV 1 - 80 - 21				80	7 x 10				



(Unit : mm)


Main Dimension						허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m		
Assembling Dimension				케이지길이 Length of Cage C	롤러수 The number of roller Z		Cz KN	Coz KN			
d	D	h	K								
1.65	3	1.4	1.5	14	5	-2	0.152	0.153	0.11		
				19	7						
				26.5	10						
				34	13						
				41.5	16						
				49	19						
				54	21						

1kN = 102kgf

A





**JV 2**

크로스 롤러 슬라이드 가이드  
Crossed – Roller Slide Guide



Specification Model	스토록크 Stroke	주 요 치 수							
		조합지수 Combination Dimension			장착치수				
		B	H	Lo	n x P	G	I	F	S
JV 2 - 30 - 5	18	12	6	30	1 x 15	7.5	5.6	2.5	M3 x 0.5
JV 2 - 45 - 8	24			45	2 x 15				
JV 2 - 60 - 11	30			60	3 x 15				
JV 2 - 75 - 13	44			75	4 x 15				
JV 2 - 90 - 16	50			90	5 x 15				
JV 2 - 105 - 18	64			105	6 x 15				
JV 2 - 120 - 21	70			120	7 x 15				
JV 2 - 135 - 23	84			135	8 x 15				
JV 2 - 150 - 26	90			150	9 x 15				
JV 2 - 165 - 29	96			165	10 x 15				
JV 2 - 180 - 32	102			180	11 x 15				

A




Main Dimension					허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m	
Assembling Dimension				케이지길이 Length of Cage C	롤러수 The number of roller Z	Cz KN	Coz KN		
d	D	h	K						
2.55	4.4	2	2	21	5	-3	0.276	0.271	
				33	8				
				45	11				
				53	13				
				65	16				
				73	18				
				85	21				
				93	23				
				105	26				
				117	29				
				129	32				

1kN = 102kgf


A

**JV 3**

크로스 롤러 슬라이드 가이드  
Crossed – Roller Slide Guide



Specification Model	스토로크 Stroke	주 요 치 수							
		조합지수 Combination Dimension			장착치수				
		B	H	Lo	n x P	G	I	F	S
JV 3 - 50 - 7	28	18	8	50	1 x 25	12.5	8.3	3.5	M4 x 0.7
JV 3 - 75 - 10	48			75	2 x 25				
JV 3 - 100 - 14	58			100	3 x 25				
JV 3 - 125 - 17	78			125	4 x 25				
JV 3 - 150 - 21	88			150	5 x 25				
JV 3 - 175 - 24	108			175	6 x 25				
JV 3 - 200 - 28	118			200	7 x 25				
JV 3 - 225 - 31	138			225	8 x 25				
JV 3 - 250 - 35	148			250	9 x 25				
JV 3 - 275 - 38	168			275	10 x 25				
JV 3 - 300 - 42	178			300	11 x 25				



(Unit : mm)

Main Dimension				허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m	
Assembling Dimension		캐이지길이 Length of Cage C	롤러수 The number of roller Z		Cz KN	Coz KN		
d	D							
3.3	6	3.1	2.5	-4	36	7	0.45	
					51	10		
					71	14		
					86	17		
					106	21		
					121	24		
					141	28		
					156	31		
					176	35		
					191	38		
					211	42		



1kN = 102kgf

A


**JV 4**

크로스 롤러 슬라이드 가이드

Crossed - Roller Slide Guide



Specification Model	스토로크 Stroke	주 요 치 수							
		조합지수 Combination Dimension		장착치수					
		B	H	Lo	n x P	G	I	F	S
JV 4 - 80 - 7	58	22	11	80	1 x 40	20	10.2	4.5	M5 x 0.8
JV 4 - 120 - 11	82			120	2 x 40				
JV 4 - 160 - 15	106			160	3 x 40				
JV 4 - 200 - 19	130			200	4 x 40				
JV 4 - 240 - 23	154			240	5 x 40				
JV 4 - 280 - 27	178			280	6 x 40				
JV 4 - 320 - 31	202			320	7 x 40				
JV 4 - 360 - 35	226			360	8 x 40				
JV 4 - 400 - 39	250			400	9 x 40				
JV 4 - 440 - 43	274			440	10 x 40				
JV 4 - 480 - 47	298			480	11 x 40				



(Unit : mm)


Main Dimension					허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m
Assembling Dimension				케이지길이 Length of Cage C	롤러수 The number of roller Z	Cz KN	Coz KN	
d	D	h	K			Cz KN	Coz KN	
4.3	8	4.2	2.5	51	7	-5	1.38	0.8
				79	11			
				107	15			
				135	19			
				163	23			
				191	27			
				219	31			
				247	35			
				275	39			
				303	43			
				331	47			

1kN = 102kgf

A


**JV 6**

크로스 롤러 슬라이드 가이드  
Crossed - Roller Slide Guide



Specification Model	스토로크 Stroke	주 요 치 수							
		조합지수 Combination Dimension		장 착 치 수					
		B	H	Lo	n x P	G	I	F	S
JV 6 - 100 - 7	56	30	15	100	1 x 50	25	14.4	6	M6 x 1.0
JV 6 - 150 - 10	96			150	2 x 50				
JV 6 - 200 - 13	136			200	3 x 50				
JV 6 - 250 - 17	156			250	4 x 50				
JV 6 - 300 - 20	196			300	5 x 50				
JV 6 - 350 - 24	216			350	6 x 50				
JV 6 - 400 - 27	256			400	7 x 50				
JV 6 - 450 - 31	276			450	8 x 50				
JV 6 - 500 - 34	316			500	9 x 50				
JV 6 - 550 - 38	336			550	10 x 50				
JV 6 - 600 - 41	376			600	11 x 50				

A



(Unit : mm)

Main Dimension				허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m
Assembling Dimension		케이지길이 Length of Cage C	롤러수 The number of roller Z		Cz KN	Coz KN	
d	D	h	K				
5.2	9.5	5.2	3	72	7	-7	3.78
				102	10		
				132	13		
				172	17		
				202	20		
				242	24		
				272	27		
				312	31		
				342	34		
				382	38		
				412	41		


1kN = 102kgf

**A**

# JV 9


크로스 롤러 슬라이드 가이드

Crossed - Roller Slide Guide



Specification Model	스토로크 Stroke	주 요 치 수							
		조합지수 Combination Dimension		장착치 수					
		B	H	Lo	n x P	G	I	F	S
JV 9 - 200 - 10	118	40	20	200	1 x 100	50	19.2	8	M8 x 1.25
JV 9 - 300 - 15	178			300	2 x 100				
JV 9 - 400 - 20	238			400	3 x 100				
JV 9 - 500 - 25	298			500	4 x 100				
JV 9 - 600 - 30	358			600	5 x 100				
JV 9 - 700 - 35	418			700	6 x 100				
JV 9 - 800 - 40	478			800	7 x 100				
JV 9 - 900 - 45	538			900	8 x 100				
JV 9 - 1000 - 50	598			1000	9 x 100				
JV 9 - 1100 - 55	658			1100	10 x 100				
JV 9 - 1200 - 60	718			1200	11 x 100				

A



(Unit : mm)


Main Dimension				허용 예압량 Permissible Preload $\delta \mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m
Assembling Dimension		케이지길이 Length of Cage C	롤러수 The number of roller Z		Cz KN	Coz KN	
d	D	h	K				
6.8	10.5	6.2	3	141	10		
				211	15		
				281	20		
				351	25		
				421	30		
				491	35	-10	9.53
				561	40		9.48
				631	45		
				701	50		
				771	55		
				841	60		3.2

1kN = 102kgf

A


**JVN B6**

크로스 롤러 슬라이드 가이드  
Crossed - Roller Slide Guide



Specification Model	스토로크 Stroke	주 요 치 수						
		조합지수 Combination Dimension		장착치 수				
		B	H	Lo	n × P	G	I	F
JVN B 6 - 100 - 7	56	31	15	100	1 × 50	25	14.2	6
JVN B 6 - 150 - 10				150	2 × 50			
JVN B 6 - 200 - 13				200	3 × 50			
JVN B 6 - 250 - 17				250	4 × 50			
JVN B 6 - 300 - 20				300	5 × 50			
JVN B 6 - 350 - 24				350	6 × 50			
JVN B 6 - 400 - 27				400	7 × 50			
JVN B 6 - 450 - 31				450	8 × 50			
JVN B 6 - 500 - 34				500	9 × 50			
JVN B 6 - 550 - 38				550	10 × 50			
JVN B 6 - 600 - 41				600	11 × 50			

A



(Unit : mm)

Main Dimension					허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m
Assembling Dimension				케이지길이 Length of Cage C		Cz KN	Coz KN	
d	D	h	K					
5.2	9.5	5.2	3	72	7	-7	3.78	1.5
				102	10			
				132	13			
				172	17			
				202	20			
				242	24			
				272	27			
				312	31			
				342	34			
				382	38			
				412	41			



1kN = 102kgf

A

**JVNB9**


크로스 롤러 슬라이드 가이드

Crossed - Roller Slide Guide



Model	Specification 스토로크 Stroke	주 요 치 수							
		조합지수 Combination Dimension			장착치수				
		B	H	Lo	n × P	G	I	F	S
JVNB 9 - 200 - 10	118	44	22	200	1 × 100	50	20.2	9	M8 × 1.25
JVNB 9 - 300 - 15	178			300	2 × 100				
JVNB 9 - 400 - 20	238			400	3 × 100				
JVNB 9 - 500 - 25	298			500	4 × 100				
JVNB 9 - 600 - 30	358			600	5 × 100				
JVNB 9 - 700 - 35	418			700	6 × 100				
JVNB 9 - 800 - 40	478			800	7 × 100				
JVNB 9 - 900 - 45	538			900	8 × 100				
JVNB 9 - 1000 - 50	598			1000	9 × 100				

A



(Unit : mm)



Main Dimension					허용예압량 Permissible Preload $\delta$ $\mu\text{m}$	기본정격하중(롤러 1개당) Basic Proper Load (Per 1 roller)		질량(레일) Weight of Rail Kg/m
Assembling Dimension				케이지길이 Length of Cage C	롤러수 The number of roller Z	Cz KN	Coz KN	
d	D	h	K			Cz KN	Coz KN	
6.8	10.5	6.2	3	141	10	-10	9.53	3.2
				211	15			
				281	20			
				351	25			
				421	30			
				491	35			
				561	40			
				631	45			
				701	50			

1kN = 102kgf


A

**JVW 1**

와이드 타입, 크로스 롤러 슬라이드 가이드  
Wide Type, Crossed-Roller Slide Guide



Model	Specification	스토로크 Stroke	D.	롤러수 The number of roller Z	주 요 치 수						
					L <sub>o</sub>	H	t	B	B <sub>1</sub>	I	Q
JVW 1 - 20 - 5	12	1.5	1.5	5	20	4.5	0.5	17	7.6	3.8	13.4
JVW 1 - 30 - 7	22			7	30						
JVW 1 - 40 - 10	27			10	40						
JVW 1 - 50 - 13	32			13	50						
JVW 1 - 60 - 16	37			16	60						
JVW 1 - 70 - 19	42			19	70						
JVW 1 - 80 - 21	52			21	80						





Main Dimension								기본정격하중 Basic Proper Load		질량(레일) Weight of Rail
n x P	G	S	d	D	h	K	Dw	Cz KN	Coz KN	Kg/m
1 x 10	5	M2 x 0.4	1.65	3	1.4	1.5	2 + 0.020	34	31	0.46
2 x 10								46	47	
3 x 10								68	78	
4 x 10								78	94	
5 x 10								96	125	
6 x 10								105	140	
7 x 10								114	156	

1KN = 102kgf


A

**JVW 2**

와이드 타입, 크로스 롤러 슬라이드 가이드  
Wide Type, Crossed-Roller Slide Guide



Specification Model	스토로크 Stroke	D <sub>a</sub>	롤러수 The number of roller Z	주 요 치 수						
				L <sub>o</sub>	H	t	B	B <sub>1</sub>	I	Q
JVW 2 - 30 - 5	18	2	5	30						
JVW 2 - 45 - 8	24		8	45						
JVW 2 - 60 - 11	30		11	60						
JVW 2 - 75 - 13	44		13	75	6.5	0.5	24	11	5.5	19
JVW 2 - 90 - 16	50		16	90						
JVW 2 - 105 - 18	64		18	105						
JVW 2 - 120 - 21	70		21	120						



(Unit : mm)



Main Dimension								<b>기본정격하중</b> Basic Proper Load	<b>질량(레일)</b> Weight of Rail	
<b>n x P</b>	<b>G</b>	<b>S</b>	<b>d</b>	<b>D</b>	<b>h</b>	<b>K</b>	<b>D<sub>w</sub></b>	<b>C<sub>z</sub> KN</b>	<b>C<sub>oz</sub> KN</b>	
1 x 15	7.5	M3 x 0.5	2.55	4.4	2	2	3 + 0.020	59	59	0.98
2 x 15								100	118	
3 x 15								118	147	
4 x 15								135	176	
5 x 15								168	235	
6 x 15								184	265	
7 x 15								199	294	

1KN = 102kgf


A

**JVW 3**

와이드 타입, 크로스 롤러 슬라이드 가이드  
Wide Type, Crossed-Roller Slide Guide



Specification Model	스토로크 Stroke	D.	롤러수 The number of roller Z	주 요 치 수						
				Lo	H	t	B	B <sub>1</sub>	I	Q
JVW 3 - 50 - 7	28	3	7	50						
JVW 3 - 75 - 10	48		10	75						
JVW 3 - 100 - 14	58		14	100						
JVW 3 - 125 - 17	78		17	125	8.5	0.5	36	16.6	8.3	29
JVW 3 - 150 - 21	88		21	150						
JVW 3 - 175 - 24	108		24	175						
JVW 3 - 200 - 28	118		28	200						





Main Dimension								기본정격하중 Basic Proper Load		질량(레일) Weight of Rail Kg/m
n x P	G	S	d	D	h	K	D_w	C_z KN	C_oz KN	
1 x 25	12.5	M4 x 0.7	3.3	6	3.1	2.5	4	180	212	1.94
2 x 25								264	353	
3 x 25								340	494	
4 x 25								376	565	
5 x 25								444	706	
6 x 25								510	847	
7 x 25								572	988	


1KN = 102kgf

**JVW 4**

와이드 타입, 크로스 롤러 슬라이드 가이드  
Wide Type, Crossed-Roller Slide Guide



Specification Model	스토로크 Stroke	D <sub>a</sub>	롤러수 The number of roller Z	주 요 치 수						
				L <sub>o</sub>	H	t	B	B <sub>1</sub>	I	Q
JVW 4 - 80 - 7	58	4	7	80	11.5	0.5	44	20.4	10.2	35
JVW 4 - 120 - 11	82		11	120						
JVW 4 - 160 - 15	106		15	160						
JVW 4 - 200 - 19	130		19	200						
JVW 4 - 240 - 23	154		23	240						
JVW 4 - 280 - 27	178		27	280						



(Unit : mm)




Main Dimension								기본정격하중 Basic Proper Load		질량(웨일) Weight of Rail Kg/m
n x P	G	S	d	D	h	K	D <sub>w</sub>	C <sub>z</sub> KN	C <sub>coz</sub> KN	
1 x 40	20	M5 x 0.8	4.3	8	4.5	2.5	5	356	435	3.36
2 x 40								522	725	
3 x 40								672	1020	
4 x 40								812	1310	
5 x 40								943	1600	
6 x 40								1070	1890	

1KN = 102Kgf

A

**JC**

롤러 케이지  
Roller Cage



Model	Specification 적용가이드 Applicable Guide	주 요 치 수 Main Dimension					기본정격하중 Basic Proper Load	
		D <sub>a</sub>	t	E	P	g	C <sub>z</sub> KN	C <sub>o_z</sub> KN
JC 1	JV1	1.5	0.2	3.5	2.5	2	0.069	21.6
JC 2	JV2	2	0.3	5	4	2.5	0.127	39.2
JC 3	JV3	3	0.4	7	5	3	0.275	87.3
JC 4	JV4	4	0.4	9	7	4.5	0.637	155
JC 6	JV6	6	0.8	13	10	6	1.76	353
JC 9	JV9	9	1.2	18	14	7.5	4.36	784

## **Crossed Roller Slide Table**



**B**


JVT 1/ 2/ 3

JVT 1-A/ 2-A/ 3-A

JVU 1/ 2/ 3/ 4/ 6/ 9

# Cross Roller Slide Table Guide

(Fig.1) Structure of cross roller rotary guide model



## Structure

Cross roller table is of high-precision, compact and linear guide instrument through addembling MENTOR cross roller linear guide JVU type between the table and base manufactured with superior precision. Rigidity and soft linear motion can be acquired since there's no elastic displacement against the load from each direction. There are JVU type and miniature version of JVT type for limited cross roller table. It is widely used for OA instruments and peripherals, precision equipments such as meters, printed circuit board hole manufacturer or slides including universal center lathe, tool grinders, internal grinding machine, small-sized surface grinder, and computerized wire-cut.

## Features

### ■ High precision

High precision with stable linear motion can be achieved by mounting uniformly-structured orbiting plane to the base of simple structure with no manufacture errors. For opposite table side, stable linear motion with high precision can be achieved by assembling MENTOR cross roller linear guide JVU type.

### ■ High rigidity

The rigidity of table and base is made to be high by integrating the component parts. Moreover, the elastic displacement is small so that high rigidity is obtained for the load from each direction.

### ■ Wide range of permissible load

A roller with heavy load rating is assembled with fine pitch. Hence it resists heavy load and has such longevity by consisting of linear guide machine with high rigidity.

### ■ Simple Installation

As the cross roller guide is assembled between the table and the base that have been processed with high precision level, the linear guide of high precision can be obtained.

### ■ Outstanding resistance to corrosion


- Stainless + light-type aluminum  
(JVWS, JVTS, JVTS-A type)

the table of JVWS type and JVTS-A type adopts aluminum material. Furthe, the rail and roller gauge adopts stainless, making it possible that product is light and highly resistant to corrosion.

### ■ Various kinds of using methods

Since theo rollers are arranged orthogonally by turns, loads from every direction applied to the table are uniformly carried.

⟨Fig.2⟩ Load direction




**Features**

JVT type



JVT-A type




JVU type

**Accuracy standards**

The height of cross roller table(T). Permissible width(W) and the level of distance of C and D sides to the fixing plane of the base are written in the dimension table.

〈Fig.3〉 Standard size

**Basic static load rationg C<sub>0</sub>**

If excessive load or impact is given to JVT and JVU type when it is stalled or in motion, there occurs permanent transformation between rolling surface and roller. Basic static load rating( $C_0$ ) is the load when the sum of permanent transformation volume of the rolling surface and roller is 0.0001 times more the diameter of the latter. (Refer to Load rating of each direction). If the sum of permanent transformation volume breaks 0.0001 times of the roller's diameter, its motion will be adversely affected. Static safety factor( $f_s$ ) to the load should be considered in order to prevent it. (Refer to Static safety factor)

## Basic dynamic load rating C

### ■ High precision

When each of JVT and JTU types in the first group is in motion, the load that does not transform its size at the direction where 90% of the first group's rated life span reaches L=100km is called basic dynamic load rating(C), which can be used for calculate life span. (Refer to Rated Life span)

## Load ratings in each direction

Load rating of JVT and JVU type is equal from all four direction including radial, reverse radial, and horizontal side. The value is written in (C) and ( $C_0$ ) in the dimension table.

## Static safety factor $f_s$

Sudden external force can be created when direct-acting system stops or is in motion due to vibration, impact or maneuvered stall. That's why the static safety factor to the applied load needs to be taken into account.

$$f_s = \left(\frac{C_0}{P_c}\right) \text{ or } f_s = \left(\frac{M_0}{M}\right)$$

$f_s$  : Static safety factor

$C_0$  : Basic static load rating

$M_0$  : Static-permissible moment (MP<sub>0</sub> · MR<sub>0</sub> · Mr<sub>0</sub>)

P<sub>c</sub> : Applied load

M : Applied moment

**■ Reference value of static safety factor**  
Static safety factor written in the <Table.1> should be used as the minimum reference value depending on each for use.

<Table.1> Reference value of static safety factor( $f_s$ )

Machine for use	Load condition	Lower limit of $f_s$
Standard industrial machine	With vibration or impact	1.0~1.3
	Without vibration or impact	2.0~3.0
Machine tools	With vibration or impact	1.0~1.5
	Without vibration or impact	2.5~7.0

## Rated life span L

The life span of cross roller table can be calculated with the following formula.

$$L_0 = \left( \frac{f_T}{f_w} \cdot \frac{C}{P_c} \right)^{\frac{10}{3}} \times 100$$

L : Rated life span (km)

(It's the total distance where 90% of the first group can reach without flaking when each of the same JVT · JVU type in the first group is put in motion under the same condition.)

C : Basic dynamic load rating (kN)

P<sub>c</sub> : Applied load (kN)

f<sub>T</sub> : Temperature factor refer to <Fig.4>

f<sub>w</sub> : Load factor refer to <table.2>


When the length and lap number of stroke is uniform, service life can be figured by using the following formula after rated life span(L) is calculated from the formula mentioned above.

$$L_h = \left( \frac{L \times 10^6}{2 \times \ell_s \times n_1 \times 60} \right)$$

### ■ f<sub>T</sub> : Temperature factor

When the environment temperature where the linear motion system is used is over 100°C, temperature factor below should be multiplied considering the possible adverse effect caused by high temperature.

<Fig.4> Temperature factor (f<sub>T</sub>)



Note) In case that environment temperature is over 100°C contact MENTOR

### ■ $f_w$ : Load factor

Shuffling machine is likely to be affected by vibration or impact during drive. While driving highspeed, particularly, it is a lot more difficult to calculate each value precisely. Therefore, when the load applied to the JVT and JVU type cannot be calculated or the impact of speed vibration is large, the load factor in the table below should be divided into the basic load rating(C) and ( $C_0$ ).

**Table.2) Load factor ( $f_w$ )**

Vibration • Impact	Velocity (V)	$f_w$
Meager	For meager speed $V \leq 0.25\text{m/s}$	1.0 ~ 1.2
	For low speed $0.25 < V \leq 1.0\text{m/s}$	1.2 ~ 1.5
Standard industrial machine	For average speed $1.0 < V \leq 2.0\text{m/s}$	1.5 ~ 2.0
Machine tools	For high speed $V > 2.0\text{m/s}$	2.0 ~ 3.5

## Cautions when using

### ■ Lubrication

- 1) To lubricate a cross roller table, use lithium soap grease or properly just like with the standard bearing.
- 2) Completely eliminate a rust preventive oil and apply a lubricant to the product before using a product.
- 3) Do not mix lubricants having different physical properties.
- 4) General lubricants may not be used at clean rooms or places exposed to regular vibrations, or under special environments such as vacuum, low temperatures and high temperatures.
- 5) Please consult with MENTOR before using the lubricants when special lubricants are to be used.

### ■ Handling

- 1) Please do not disassemble a product as the separation of components from product is responsible for inflow of dust into the product or poor assembling accuracy in mounting faces of the respective components.
- 2) The cross roller table may be damaged if a cross roller table is dropped or impacted. Please be careful not to impact the product as the impact may damage functions of the product although the product looks normal when an impact is applied to a product.


### ■ Additional process of table & base

- 1) Be careful not to let any chips put into the cross roller guide parts.
- 2) Fixing holes should be blocked, not penetrated. It also can be manufactured according to specific designation.  
Clearance of the cross roller table is already adjusted with appropriate preload, thus do not touch the clearance adjust screws.

### ■ Distortion of a cage

Although roller-sustaining cage moves with sharp accuracy, distortion can occur due to a moment or mechanic vibrations. When such distortion is the problem, using miniature version of linear rail system is recommended.


B





# JVT 1

베이스 탭 타입  
Base Tap Type

B



Specification Model	주 요 치 수 Main Dimension						테 이 블 면 치 수 Table Surface Dimension							
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L —	질량 Weight g	테이블장착탭위치 Table Tap Position					P <sub>1</sub>	n X P <sub>1</sub>	Q <sub>1</sub>	G <sub>1</sub>
						Q	P	n X P	G	S				
JVT 1 - 25	12			25	23		18	1 x 18				1 x 10		
JVT 1 - 35	18			35	33		28	1 x 28		3.5			2 x 10	
JVT 1 - 45	25			45	43		20	1 x 20				3 x 10		
JVT 1 - 55	32	20	8	55	53	14	30	1 x 30	12.5	M2.6 x 0.45	10	4 x 10	12.4	7.5
JVT 1 - 65	40			65	63		20	2 x 20				5 x 10		
JVT 1 - 75	45			75	73		30	1 x 30	22.5			6 x 10		
JVT 1 - 85	50			85	83		30	2 x 30	12.5			7 x 10		



정도 Accuracy

각방향의 모멘트 Moment in each direction

(Unit : mm)


측면치수 Side Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position					기본정격하중 Basic Proper Load			정격허용모멘트 Regular Permissible Moment			정도 $\mu\text{m}$ Accuracy	
B <sub>1</sub>	B <sub>2</sub>	T	Y	C	c	S <sub>1</sub>	P <sub>1</sub>	n X P <sub>1</sub>	g <sub>1</sub>	롤러수 The number of roller Z	C KN	C <sub>o</sub> KN	MA N.m	MB N.m	Mc N.m	C	D		
7.5	3.5	4	6.6	5.5	M2	M2.6 X 0.45	10	7.5	2 x 7.5	5	5	0.46	0.61	2.29	1.52	1.25	4		
								2 x 10		7	0.63	0.92	3.44	2.62	2.32				
								3 x 10		10	0.95	1.53	5.73	4.14	4.53				
								4 x 10		12	1.09	1.83	6.87	5.92	6.41	2			
								5 x 10		14	1.23	2.14	8.02	8.08	8.62				
								6 x 10		18	1.50	2.75	10.3	13.3	14.0				
								7 x 10		20	1.63	3.05	11.5	16.4	17.2				

1KN ≈ 102kgf 1N · m ≈ 0.102Kgf



# JVT 2

베이스 탭 타입  
Base Tap Type

B



Model	Specification	주 요 치 수 Main Dimension				테 이 블 면 치 수 Table Surface Dimension										
		최대 스토roke Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>o</sub>	질량 Weight g	테이블장착탭위치 Table Tap Position					P <sub>1</sub>	n X P <sub>1</sub>	Q <sub>1</sub>	G <sub>1</sub>	
JVT 2- 35	18			35	78		28	1 x 28		3.5			1 x 15			
JVT 2- 50	30			50	114		43	1 x 43					2 x 15			
JVT 2- 65	40			65	150		30	1 x 30					3 x 15			
JVT 2- 80	50	30	12	80	186	22	45	1 x 45	17.5	M3 x 0.5	15	4 x 15	20	10		
JVT 2- 95	60			95	222		30	2 x 30					5 x 15			
JVT 2- 110	70			110	258		45	1 x 45	32.5				6 x 15			
JVT 2- 125	80			125	294		45	2 x 45	17.5				7 x 15			



정도 Accuracy



각방향의 모멘트 Moment in each direction


(Unit : mm)

측면치수 Side Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position					기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Moment			정도 $\mu m$ Accuracy	
B <sub>1</sub>	B <sub>2</sub>	T	Y	C	c	S <sub>1</sub>	P <sub>1</sub>	n X P <sub>1</sub>	g <sub>1</sub>	롤러수 The number of roller Z	C KN	C <sub>o</sub> KN	M <sub>A</sub> N.m	M <sub>B</sub> N.m	M <sub>C</sub> N.m	C	D	
11.5	5.5	6	12	8.5	M2	M3 x 0.5	15	20	1 x 20	7.5	5	0.84	1.09	7.06	4.32	3.55	4	4
								2 x 15			7	1.16	1.63	10.6	7.45	6.59		
								3 x 15			9	1.46	2.17	14.1	11.8	10.5		
								4 x 15			12	2.01	3.26	21.2	16.8	18.2		
								5 x 15			14	2.26	3.80	24.7	23.0	24.5	2	5
								6 x 15			17	2.51	4.34	28.2	37.9	35.7		
								7 x 15			19	2.76	4.89	31.8	46.7	44.3		



1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf

# JVT 3

B  
베이스 탭 타입  
Base Tap Type



Model	주 요 치 수 Main Dimension					테 이 블 면 치 수 Table Surface Dimension							
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>o</sub>	질량 Weight g	테이블장착탭위치 Table Tap Position				P <sub>1</sub>	n X P <sub>1</sub>	Q <sub>1</sub>	G <sub>1</sub>
JVT 3 - 55	30			55	229	40	1 x 40				1 x 25		
JVT 3 - 80	45			80	337	65	1 x 65		7.5		2 x 25		
JVT 3 - 105	60			105	445	50	1 x 50				3 x 25		
JVT 3 - 130	75	40	16	130	553	75	1 x 75	27.5	M4 x 0.7	25	4 x 25	28.4	15
JVT 3 - 155	90			155	661	50	2 x 50				5 x 25		
JVT 3 - 180	105			180	769	75	1 x 75	52.5			6 x 25		
JVT 3 - 205	130			205	877	75	2 x 75	27.5			7 x 25		



정도 Accuracy



각방향의 모멘트 Moment in each direction


출면치수 Side Dimension								베이스면 치수 정착구멍 위치 Base Dimension & Hole Position					기본정격하중 Basic Proper Load			정격허용모멘트 Regular Permissible Moment			(Unit : mm)	
B <sub>1</sub>	B <sub>2</sub>	T	Y	C	c	S <sub>1</sub>	P <sub>1</sub>	n × P <sub>1</sub>	g <sub>1</sub>	롤러수 The number of roller Z	C KN	C <sub>o</sub> KN	MA N.m	MB N.m	Mc N.m	C	D			
15.5	7.5	8	16	11.5	M2	M4 x 0.7	25	35	1 x 35	10	6	2.71	3.67	31.9	12.2	13.9	2	5		
								2 x 25	15	10	4.06	6.11	53.1	33.1	36.2					
								3 x 25		13	4.68	7.33	63.8	64.6	59.8	3	6			
								4 x 25		17	5.87	9.77	85	107	100					
								5 x 25		20	6.98	12.2	106	131	138					
								6 x 25		24	8.05	14.7	128	189	196					
								7 x 25		26	8.57	15.9	138	222	230					

1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf



# JVT 1-A

B


베이스 홀 타입  
Base Hole Type



Specification Model	주 요 치 수 Main Dimension					테 이 블 면 치 수 Table Surface Dimension							
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>a</sub>	질량 Weight g	테이블장착발위치 Table Tap Position					P <sub>1</sub>	n X P <sub>1</sub>	Q <sub>1</sub>
JVT 1 - 25 - A	12	20	8	25	23	Q	18	1 x 18	3.5	M2.6 x 0.45	1 x 10	12.4	7.5
JVT 1 - 35 - A	18			35	32	P	28	1 x 28			2 x 10		
JVT 1 - 45 - A	25			45	42	n	20	1 x 20			3 x 10		
JVT 1 - 55 - A	32			55	52	X	30	1 x 30	12.5		4 x 10		
JVT 1 - 65 - A	40			65	62	P	20	2 x 20	5 x 10				
JVT 1 - 75 - A	45			75	72	G	30	1 x 30	22.5		6 x 10		
JVT 1 - 85 - A	50			85	82	S	30	2 x 30	12.5		7 x 10		



정도 Accuracy



각방향의 모멘트 Moment in each direction

(Unit : mm)


측면치수 Side Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position				기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Moment			정도 μm Accuracy	
B <sub>1</sub>	B <sub>2</sub>	T	Y	C	c	d x D x h	ℓ <sub>1</sub>	ℓ <sub>2</sub>	g <sub>1</sub>	롤러수 The number of roller Z	C KN	C <sub>o</sub> KN	M <sub>A</sub> N.m	M <sub>B</sub> N.m	M <sub>C</sub> N.m	C	D
7.5	3.5	4	6.6	5.5	M2	2.5 x 4.1 x 2.2	-	18	3.5	5	0.46	0.61	2.29	1.52	1.25	4	5
							-	25	5	7	0.63	0.92	3.44	2.62	2.32		
							25	38	3.5	10	0.95	1.53	5.73	4.14	4.53		
							29	48	3.5	12	1.09	1.83	6.87	5.92	6.41	2	5
							31	55	5	14	1.23	2.14	8.02	8.08	8.62		
							35	65	5	18	1.50	2.75	10.3	13.3	14.0		
							40	75	5	20	1.63	3.05	11.5	16.4	17.2		

1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf



# JVT 2-A

B


베이스 홀 타입  
Base Hole Type



Specification Model	주 요 치 수 Main Dimension					테이블 면 치 수 Table Surface Dimension								
	최대 스로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>a</sub>	질량 Weight g	테이블장착타입위치 Table Tap Position					P <sub>1</sub>	n X P <sub>1</sub>	Q <sub>1</sub>	G <sub>1</sub>
						Q	P	n X P	G	S				
JVT 2 - 35 - A	18			35	78		28	1 x 28	3.5			1 x 15		
JVT 2 - 50 - A	30			50	113		43	1 x 43				2 x 15		
JVT 2 - 65 - A	40			65	147		30	1 x 30				3 x 15		
JVT 2 - 80 - A	50	30	12	80	186	22	45	1 x 45	17.5	M3 x 0.5	15	4 x 15	20	10
JVT 2 - 95 - A	60			95	217		30	2 x 30				5 x 15		
JVT 2 - 110 - A	70			110	254		45	1 x 45				6 x 15		
JVT 2 - 125 - A	80			125	287		45	2 x 45	17.5			7 x 15		



정도 Accuracy



각방향의 모멘트 Moment in each direction

(Unit : mm)


측면치수 Side Dimension						베이스면 치수 장착구멍 위치 Base Dimension & Hole Position				기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Moment			정도 $\mu m$ Accuracy		
B <sub>1</sub>	B <sub>2</sub>	T	Y	C	c	d x D x h	l <sub>1</sub>	l <sub>2</sub>	g <sub>1</sub>	롤러수 The number of roller Z	C KN	C <sub>o</sub> KN	MA N.m	MB N.m	Mc N.m	C	D
11.5	5.5	6	12	8.5	M2	3.5 x 6 x 3.2	-	25	5	5	0.84	1.09	7.06	4.32	3.55	4	4
							-	35	7.5	7	1.16	1.63	10.6	7.45	6.59		
							33	55	5	9	1.46	2.17	14.1	11.8	10.5	2	5
							40	70	5	12	2.01	3.26	21.2	16.8	18.2		
							45	85	5	14	2.26	3.80	24.7	23.0	24.5		
							50	95	7.5	17	2.51	4.34	28.2	37.9	35.7		
							55	110	7.5	19	2.76	4.89	31.8	46.7	44.3		

1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf



# JVT 3-A

B


베이스 홀 타입  
Base Hole Type



Model	주 요 치 수 Main Dimension					테 이 블 면 치 수 Table Surface Dimension								
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L	질량 Weight g	테이블장착탭위치 Table Tap Position					P <sub>1</sub>	n X P <sub>1</sub>	Q <sub>1</sub>	G <sub>1</sub>
	Q	P	n X P	G	S									
JVT 3 - 55 - A	30			55	226		40	1 X 40				1 x 25		
JVT 3 - 80 - A	45			80	334		65	1 x 65	7.5			2 x 25		
JVT 3 - 105 - A	60			105	442		50	1 x 50				3 x 25		
JVT 3 - 130 - A	75	40	16	130	550	30	75	1 x 75	27.5	M4 x 0.7	25	4 x 25	28.4	15
JVT 3 - 155 - A	90			155	658		50	2 x 50				5 x 25		
JVT 3 - 180 - A	105			180	766		75	1 x 75	52.5			6 x 25		
JVT 3 - 205 - A	130			205	874		75	2 x 75	27.5			7 x 25		



정도 Accuracy



각방향의 모멘트 Moment in each direction



(Unit : mm)

측면치수 Side Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position					기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Moment			정도 $\mu\text{m}$ Accuracy	
B <sub>1</sub>	B <sub>2</sub>	T	Y	C	c	d × D x h	l <sub>1</sub>	l <sub>2</sub>	g <sub>1</sub>	롤러수 The number of roller Z	C KN	C <sub>o</sub> KN	MA N.m	MB N.m	Mc N.m	C	D	
15.5	7.5	8	16	11.5	M2	4.5 x 7.5 x 4.2	-	40	7.5	6	2.71	3.67	31.9	12.2	13.9	2	5	
							43	68	6	10	4.06	6.11	53.1	33.1	36.2			
							55	90	7.5	13	4.68	7.33	63.8	64.6	59.8	3	6	
							65	115		17	5.87	9.77	85	107	100			
							95	140		20	6.98	12.2	106	131	138			
							85	165		24	8.05	14.7	128	189	196			
							90	190		26	8.57	15.9	138	222	230			



1KN ≈ 102Kgf    1N · m ≈ 0.102Kgf

# JVU 1

B  
소형 스테이지  
Miniature Stage



Model	주 요 치 수 Main Dimension					테 이 블 면 치 수 Table Surface Dimension							
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>o</sub>	질량 Weight g	테이블장착탭위치 Table Tap Position				테이블장착탭위치 Table Tap Position			
						Q	n X P <sub>1</sub>	G <sub>1</sub>	G <sub>2</sub>	T	Q <sub>1</sub>	n X P <sub>2</sub>	G
JVU 1 - 25	12			25	85		-		2.5			1 x 10	
JVU 1 - 35	18			35	117		1 x 10		4.5			2 x 10	
JVU 1 - 45	25			45	149		2 x 10		6			3 x 10	
JVU 1 - 55	32	30	17	55	181	10	3 x 10	12.5	7.5	M2 x 0.4	18	4 x 10	7.5
JVU 1 - 65	40			65	213		4 x 10		8.5			5 x 10	12.0
JVU 1 - 75	45			75	245		5 x 10		11			6 x 10	2.5
JVU 1 - 85	50			85	277		6 x 10		13.5			7 x 10	M2 x 4



정도 Accuracy



각방향의 모멘트 Moment in each direction

(Unit : mm)



Table Surface Dimension					베이스면 치수 장착구멍 위치 Base Dimension & Hole Position							롤러수 The number of roller Z	기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Momenet			정도 $\mu\text{m}$ Accuracy		
B <sub>2</sub>	B <sub>1</sub>	K	d x D x h	D <sub>1</sub>	C	t <sub>3</sub>	Q <sub>2</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>	g	C	Co KN	MA N.m	MB N.m	Mc N.m	C	D	
11	5.5	6.5	2.55 x 4.1 x 2.5	4.1	9	M2	22	18	-	-	-	3.5	5	0.46	0.61	4.12	1.52	1.25	4	5
								28	-	-	-		7	0.63	0.92	6.18	2.62	2.32		
								38	-	-	-		10	0.95	1.53	10.3	4.14	4.53		
								48	28	-	-		12	1.09	1.83	12.4	5.92	6.41		
								58	38	-	-		14	1.23	2.14	14.4	8.08	8.62		
								68	48	-	-		18	1.50	2.75	18.6	13.3	14.0		
								78	58	-	-		20	1.63	3.05	20.6	16.4	17.2		

1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf



# JVU 2

소형 스테이지  
Miniature Stage


B



Specification Model	주 요 차 수 Main Dimension					테이블 면 차 수 Table Surface Dimension										
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>c</sub>	질량 Weight g	테이블장착탭위치 Table Tap Position					테이블장착탭위치 Table Tap Position					
						Q	n X <sub>P</sub>	G <sub>1</sub>	G <sub>2</sub>	T	Q <sub>1</sub>	n X <sub>P<sub>2</sub></sub>	G	s <sub>1</sub>	t <sub>1</sub>	m <sub>ℓ</sub> x x
JVU 2 - 35	18			35	199		-		3			1 x 15				
JVU 2 - 50	30			50	278		1 x 15		4.5			2 x 15				
JVU 2 - 65	40			65	357		2 x 15		7			3 x 15				
JVU 2 - 80	50	40	21	80	436	15	3 x 15	17.5	9.5	M3 x 0.5	25	4 x 15	10	16.0	3.4	M2 x 4
JVU 2 - 95	60			95	515		4 x 15		12			5 x 15				
JVU 2 - 110	70			110	594		5 x 15		14.5			6 x 15				
JVU 2 - 125	80			125	673		6 x 15		17			7 x 15				



정도 Accuracy



각방향의 모멘트 Moment in each direction



Table Surface Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position							롤러수 The number of roller Z	기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Moment			정도 $\mu\text{m}$ Accuracy	
B <sub>2</sub>	B <sub>1</sub>	K	d x D x h	D <sub>1</sub>	C	t <sub>3</sub>	Q <sub>2</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>	g	C KN	Co KN	MA N.m	MB N.m	Mc N.m	C	D		
14	6.5	7.5	3.5 x 6 x 3.5	6	11	M3	30	25	-	-	-	5	5	0.84	1.09	9.77	4.32	3.55	4	4	
								40	-	-	-		7	1.16	1.63	14.7	7.45	6.59			
								55	-	-	-		9	1.46	2.17	19.5	11.8	10.6	2	2	
								70	40	-	-		12	2.01	3.26	29.3	16.9	18.2			
								85	55	-	-		14	2.26	3.80	34.2	23	24.5	5	5	
								100	70	-	-		17	2.51	4.34	39.1	37.9	35.7			
								115	85	-	-		19	2.76	4.89	44.0	46.7	44.3	3	6	

1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf


# JVU 3

B


소형 스테이지  
Miniature Stage



Specification Model	주 요 치 수 Main Dimension					테이블 면 치 수 Table Surface Dimension							
	최대 스트roke Max Stroke	폭 Width W $\pm 0.1$	높이 Height B $\pm 0.1$	길이 Length L <sub>c</sub>	질량 Weight g	테이블장착탭위치 Table Tap Position				테이블장착탭위치 Table Tap Position			
						Q	$n_X P_1$	G <sub>1</sub>	G <sub>2</sub>	T	Q <sub>1</sub>	$n_X P_2$	
JVU 3 - 55	30			55	570		-		5.5		1 x 25		
JVU 3 - 80	45			80	825		1 x 25		10.5		2 x 25		
JVU 3 - 105	60			105	1080		2 x 25		15.5		3 x 25		
JVU 3 - 130	75	60	28	130	1335	25	3 x 25	27.5	20.5	M4 x 0.7	39	4 x 25	15
JVU 3 - 155	90			155	1590		4 x 25		25.5		5 x 25		
JVU 3 - 180	105			180	1845		5 x 25		30.5		6 x 25		
JVU 3 - 205	130			205	2100		6 x 25		30.5		7 x 25		



B



정도 Accuracy





각방향의 모멘트 Moment in each direction

(Unit : mm)



Table Surface Dimension										베이스면 치수 장착구멍 위치 Base Dimension & Hole Position				롤러수 The number of roller Z	기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Moment			정도 $\mu\text{m}$ Accuracy	
B <sub>2</sub>	B <sub>1</sub>	K	d x D x h	D <sub>1</sub>	C	t <sub>3</sub>	Q <sub>2</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>	g	C KN	Co KN	MA N.m	MB N.m	Mc N.m	C	D		
18.5	9	10	4.5 x 7.5 x 5	7.5	15	M4	40	35	-	-	-	10	6	2.71	3.67	51.3	12.2	13.9	2	5	
								60	-	-	-			4.06	6.11	85.5	33.1	36.2			
								85	-	-	-		13	4.68	7.33	103	64.6	59.8	6	7	
								110	-	-	-			5.87	9.77	137	107	100			
								135	-	85	-		20	6.98	12.2	171	131	138			
								160	-	110	-			8.05	14.7	205	189	196			
								185	85	135	-		26	8.57	15.9	222	222	230			
														1KN ≈ 102Kgf	1N · m ≈ 0.102Kgf						

# JVU 4


B  
소형 스테이지  
Miniature Stage



Specification Model	주 요 차 수 Main Dimension					테이블 면 차 수 Table Surface Dimension										
	최대 스트roke Max Stroke	폭 Width W $\pm 0.1$	높이 Height B $\pm 0.1$	길이 Length $L_o$	질량 Weight g	테이블장착탭위치 Table Tap Position					테이블장착탭위치 Table Tap Position					
						Q	$n X_P$	$G_1$	$G_2$	T	$Q_1$	$n X_{P_2}$	G	$s_1$	$t_1$	$m_x \ell$
JVU 4 - 85	50	80	35	85	1500		-		10.5			1 x 40				
JVU 4 - 125				125	2310		1 x 40		18			2 x 40				
JVU 4 - 165				165	3120	40	2 x 40		23		M5 x 0.8	3 x 40		22.5	55	6.5 M3 x 6
JVU 4 - 205				205	3930		3 x 40		30.5			4 x 40				
JVU 4 - 245				245	4740		4 x 40		38			5 x 40				
JVU 4 - 285				285	5550		5 x 40		43			6 x 40				



정도 Accuracy



각방향의 모멘트 Moment in each direction

(Unit : mm)



Table Surface Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position							롤러수 The number of roller Z	기본정격하중 Basic Proper Load		정격하용모멘트 Regular Permissible Momenet		정도 μ Accuracy	
B <sub>2</sub>	B <sub>1</sub>	K	d x D x h	D <sub>1</sub>	C	t <sub>3</sub>	Q <sub>2</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>	g	C KN	Co KN	MA N.m	MB N.m	Mc N.m	C	D	
24	10.5	5.5 x 9.5 x 6	9.5 18.5 M4 60	22.5	65	-	-	-	-	10	7	5.90	8.11	162	64.9	57.4	2	5		
					80	-	-	-	-		11	8.82	13.5	270	147	134		6		
					120	-	-	-	-		14	11.5	18.9	378	200	214				
					160	80	-	-	-		18	14.0	24.3	486	330	347	3			
					200	120	-	-	-		22	16.3	29.7	594	492	513		7		
					240	160	-	-	-		26	18.6	35.1	703	687	711				

1KN ≈ 102Kgf 1N · m ≈ 0.102Kgf



# JVU 6

B


소형 스테이지  
Miniature Stage



Specification Model	주 요 치 수 Main Dimension				테 이 블 면 치 수 Table Surface Dimension													
	최대 스트roke Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>o</sub>	질량 Weight kg	테이블장착탭위치 Table Tap Position					테이블장착탭위치 Table Tap Position							
						Q	n X P	G <sub>1</sub>	G <sub>2</sub>	T	Q <sub>1</sub>	n X P <sub>2</sub>	G	s <sub>1</sub>	s <sub>2</sub>	t <sub>1</sub>	t <sub>2</sub>	m <sub>x</sub> <sub>l</sub>
JVU 6 - 110	60			110	3.2		-		16			1 x 50						
JVU 6 - 160	95			160	4.6		1 x 50		23.5			2 x 50						
JVU 6 - 210	130			210	6		2 x 50		31			3 x 50						
JVU 6 - 260	165	100	45	260	7.4	50	3 x 50	55	38.5	M6	63	4 x 50	30	60	92	8	15	M4 x 8
JVU 6 - 310	200			310	8.7		4 x 50		46			5 x 50						
JVU 6 - 360	235			360	10.1		5 x 50		53.5			6 x 50						
JVU 6 - 410	265			410	11.5		6 x 50		63			7 x 50						



정도 Accuracy



각방향의 모멘트 Moment in each direction

(Unit : mm)



Table Surface Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position							롤러수 The number of roller Z	기본정격하중 Basic Proper Load		정격허용모멘트 Regular Permissible Momnet		정도 $\mu\text{m}$ Accuracy	
B <sub>2</sub>	B <sub>1</sub>	K	d x D x h	D <sub>1</sub>	C	t <sub>3</sub>	Q <sub>2</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>	g	C KN	Co KN	M <sub>A</sub> N.m	M <sub>B</sub> N.m	M <sub>C</sub> N.m	C	D	
31	13	15	7 x 11 x 7	11	23.5	M5	60	90	-	-	-	10	6	16.4	22.7	510	150	172	3	6
								140	-	-	-			20.5	30.2	680	410	367	3	6
								190	-	90	-			28.2	45.3	1020	800	740	3	7
								240	-	140	-			35.3	60.5	1360	1040	1100	3	7
								290	-	190	-			38.8	68.0	1530	1630	1540	4	8
								340	140	240	-			45.3	83.1	1870	1970	2050	4	8
								390	190	290	-			51.6	98.3	2210	2750	2840	4	8

1KN ≈ 102Kgf    1N · m ≈ 0.102Kgf



# JVU 9

B


소형 스테이지  
Miniature Stage



Specification Model	주 요 차 수 Main Dimension					테이블 면 치수 Table Surface Dimension												
	최대 스트로크 Max Stroke	폭 Width W ±0.1	높이 Height B ±0.1	길이 Length L <sub>o</sub>	질량 Weight kg	테이블장착탭위치 Table Tap Position						테이블장착탭위치 Table Tap Position						
						Q	n X P	G <sub>1</sub>	G <sub>2</sub>	T	Q <sub>1</sub>	n X P <sub>2</sub>	G	s <sub>1</sub>	s <sub>2</sub>	t <sub>1</sub>	t <sub>2</sub>	m X l
JVU 9 - 210	130			210	12		-		27			1 x 100						
JVU 9 - 310	180			310	17.6		1 x 100		52			2 x 100						
JVU 9 - 410	350			410	23.2		2 x 100					3 x 100						
JVU 9 - 510	450	145	60	510	28.8	85	3 x 100	105	M8	96	4 x 100	55	90	135	11	20	M4 x 8	
JVU 9 - 610	550			610	34.4		4 x 100		17			5 x 100						
JVU 9 - 710	650			710	40		5 x 100					6 x 100						
JVU 9 - 810	750			810	45.6		6 x 100					7 x 100						



정도 Accuracy




각방향의 모멘트 Moment in each direction

(Unit : mm)

Table Surface Dimension							베이스면 치수 장착구멍 위치 Base Dimension & Hole Position							롤러수 The number of roller Z	기본정격하중 Basic Proper Load		정격하용모멘트 Regular Permissible Moment			정도 $\mu\text{m}$ Accuracy	
B <sub>2</sub>	B <sub>1</sub>	K	d x D x h	D <sub>1</sub>	C	t <sub>3</sub>	Q <sub>2</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>	g	C KN	C <sub>o</sub> KN	MA N.m	MB N.m	Mc N.m	C	D		
43	16	21	9 x 14 x 9	14	32	M6	90	100	-	-	-	55	9	52.3	75.8	2730	1440	1290	3	7	
								200	-	-	-		14	81.1	133	4780	2810	2990	3	7	
								300	-	100	-		15	81.1	133	4780	3660	3420	4	8	
								400	-	200	-		19	98.7	171	6140	5710	5410	4	8	
								500	100	300	-		22	115	208	7500	6910	7200	4	9	
								600	200	400	-		26	131	246	8870	9640	9980	4	9	
								700	300	500	100		29	139	265	9550	12800	12400	5	10	

1KN ≈ 102Kgf    1N · m ≈ 0.102Kgf

B



## **Motorized Stage**



### **JMA Series(Motorized Alignment Stage)**

JMA-120  
JMA-180  
JMA-200  
JMA-300

### **JMU Series(Motorized XYR Stage)**

JMU-100  
JMU-120  
JMU-150  
JMU-200

### **JMSX Series (Linear Stage)**

JMSX-40  
JMSX-60

### **JMTX Series (Linear Stage)**

JMTX-6060  
JMTX-6060  
JMTX-6070

### **JMX Series (Linear Stage)**

JMX-40  
JMX-60  
JMX-80  
JMX-812  
JMX-816

### **JMHZ Series (Horizontal Z Stage)**

JMHZ-60  
JMHZ-80  
JMHZ-120  
JMHZ-200

### **JMR Series(Rotary Stage)**


JMR-60  
JMR-80  
JMR-100  
JMR-120  
JMR-150

### **JMG / JMT Series(Motorized Goniometer Stage)**

JMG-7070  
JMG-70101  
JMG2-7070  
JMT-100

# Motorized Alignment Stage JMA

C



## Structure

MENTOR's motorized alignment stage module type JMA is a low-section and large-sized precision positioning stage in which alignment module having an angle adjustment mechanism is arranged on the same plane, and can perform XYθ Motion.

## Features

### ■ Realization of diversified operations

Not only linear motion in the XY direction but also swing motion can be performed. In the case of swing motion, especially, an optional desired position can be set as the center of swing. This can achieve diversified operation.

### ■ High accuracy, rigidity, and reliability

Alignment module is designed on a basic of precision position table, high-rigidity crossed roller bearing, and linear way to obtain high accuracy, high rigidity, and high reliability.

### ■ Optimally applicable to large equipment

A combination of alignment module with an aluminum alloy stage and base can configure a large stage. Alignment module can be easily applicable to a larger than the dimensions described in the catalog. Consult MENTOR about it if necessary.


### ■ Hollow structure

The stage and base have a hollow structure with a large diameter. This is useful for the measurement of transmitted light from the bottom side, cord wiring of machines and equipment, etc.

## Example of motion specification

*Achievement of diversified movements : To achieve XY motion and  $\theta$  motion (swing motion) at the same moment, a combination of XY positioning table and  $\theta$  stage is normally required. However, MENTOR motorized alignment stage module type adopting alignment module enables these movements with a low profile single stage.*

# Motorized 3Axis Alignment Stage – Feed formula



## Feed formula

As expression below to find the relative feed rate of each axis to obtain the arbitrary rotation angle  $\delta\theta$  table.

$$\delta X_1 : \delta X_1 = R \cos(\delta\theta + \theta X_1 + \theta O) - R \cos(\theta X_1 + \theta O) - \text{식(1)}$$

$$\delta X_2 : \delta X_2 = R \cos(\delta\theta + \theta X_2 + \theta O) - R \cos(\theta X_2 + \theta O) - \text{식(2)}$$

$$\delta Y : \delta Y = R \sin(\delta\theta + \theta Y + \theta O) - R \sin(\theta Y + \theta O) - \text{식(3)}$$

$\delta X_1$  :  $X_1$  relative feed amount of axis (mm)

$\delta X_2$  :  $X_2$  relative feed amount of axis (mm)

$\delta Y$  :  $Y$  relative feed amount of axis (mm)

$\theta X_1$  : Angle of Cross Roller Bearing center, which is connected to the  $X_1$  axis ( $^{\circ}$ ) =  $135^{\circ}$

$\theta X_2$  : Angle of Cross Roller Bearing center, which is connected to the  $X_2$  axis ( $^{\circ}$ ) =  $225^{\circ}$

$\theta Y$  : Angle of Cross Roller Bearing center that is connected to the  $Y$ -axis ( $^{\circ}$ ) =  $45^{\circ}$

$\theta O$  : Initial position angle ( $^{\circ}$ )

$\delta\theta$  : Request rotation angle ( $^{\circ}$ )

R : Connected to each axis the Cross Roller Bearing central radius (mm)

(See Product Parameter table)

## Product parameter table

Type	R	$\theta Y$	$\theta X_1$	$\theta X_2$
JMA-200	90	$45^{\circ}$	$135^{\circ}$	$225^{\circ}$
JMA-300	155			
JMA-400	207.5			

Final calculation value

(Unit : mm)

구동축	상대 이송량			
	Case (a)		Case (b)	
	X-방향 +1mm	Y-방향 + 0.5mm	$\theta$ -방향 +2°	$\theta$ -방향 -0.3°
$X_1$	1 (+1)	0 (0)	-3.7583 (-2.7583)	0.5550 (2.2033)
	1 (+1)	0 (0)	3.8918 (+4.8918)	-0.5921 (+4.2997)
$X_2$	0 (0)	0.5 (-0.5)	3.7583 (+4.2583)	-0.5550 (+3.9733)
$Y$				

## Feed formula

### ① Motor

AC Servo Motor : SGMAH-A5A (Yaskawa, 50W)

Encoder : 2048 Pulse/Revolution

### ② Ball Screw

Ø10 , Lead 2

### ③ Resolution

$$\text{Resolution} = \frac{\text{Ball Screw Lead}}{\text{Encoder Line}} = \frac{2}{2048} = 0,0009765\text{mm}$$

### ④ Motion Profile

When operating as follows Carriage Plate in the origin initial position on the figure left page is to determine the feed rate of each axis

- (a) X-axis + 1mm, Y-axis + 0.5mm move parallel
- (b) Carriage Plate In central rotation center is rotated + 2°
- (c) Rotate -0.3 ° from the state of (b)

### ⑤ Examples of feed rate calculation

- (a) X-axis + 1mm, Y-axis + 0.5mm move parallel
- ④ Feed X-axis

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{1}{2} \times 2048 = 1024$$

► Therefore  $X_1$ , sending only 1024 Pulse in the same direction by  $X_2$  axis synchronization.

### ⑥ Feed Y-axis

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{0.5}{2} \times 2048 = 512$$

► Therefore, I will send only 512 Pulse in the Y-axis + direction.

- (b) Carriage Plate In central rotation center is rotated + 2°

$$\theta X_1 = 135^\circ \quad \theta X_2 = 225^\circ$$

$$\theta Y = 45^\circ \quad R = 155$$

In addition, depending on the initial conditions of Motion

$$\theta O = 0^\circ \quad \delta\theta = 2^\circ$$

Equation 1 above conditions, Equation 2, and substituting in equation 3,

$$\delta X_1 = 155\cos(2+135+0)-155\cos(135+0)=-3.7583\text{mm}$$

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{-3.7583}{2} \times 2048 = -3,848.50$$

► Therefore,  $X_1$  axis - direction to send only 3848.50 Pulse.

$$\delta X_2 = 155\cos(2+225+0)-155\cos(225+0)= 3.8918\text{mm}$$

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{3.8918}{2} \times 2048 = 3,985.20$$

► Therefore, send only 3985.20 Pulse to  $X_2$  axis + direction.

$$\delta Y = 155\sin(2+45+0)-155\sin(45+0)= 3.7583\text{mm}$$

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{3.7583}{2} \times 2048 = 3,848.50$$

► Therefore, send only 3848.50 Pulse in the Y-axis + direction.

- (c) Rotate -0.3 ° in the state of (b)

The condition (b)

$$\theta O = 2^\circ$$

$$\delta\theta = -0.3^\circ$$

Equation 1 above conditions, Equation 2, and substituting in equation 3,

$$\delta X_1 = 155\cos(-0.3+135+2)-155\cos(135+2)=0.5550\text{mm}$$

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{0.5550}{2} \times 2048 = 568.32$$

► Therefore, send only 568.32 Pulse to  $X_1$  axis + direction.

$$\delta X_2 = 155\cos(-0.3+225+2)-155\cos(225+2)= -0.5921\text{mm}$$

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{-0.5921}{2} \times 2048 = -606.31$$

► Therefore,  $X_2$  axis - direction to send only 606.31 Pulse.

$$\delta Y = 155\sin(-0.3+45+2)-155\sin(45+2)=-0.5550\text{mm}$$

$$\text{Pulse} = \frac{\text{Request Feed}}{\text{Ball Screw Lead}} \times \text{Encoder\_Line} = \frac{-0.5550}{2} \times 2048 = -568.32$$

► Therefore, Y-axis - direction to send only 568.32 Pulse.


C

## JMA-Series / Motorized Stage

**JMA**

## Model Selection

1) 2) 3) 4)


**JMA-200-B5-O**

1) Axis	2) Table Size	3) Grade of Ball Screw	4) Motor
JMA : UVW- stage	120 : 120x120mm 180 : 180x180mm 200 : 200x200mm 300 : 300x300mm OP : Make to Order	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O 42 : Oriental Motor (5Phase) S 42 : Sanyo (2Phase) E 42 : Ezi-Servo Y 40 : Yaskawa Servo M 40: Mitsubishi Servo X 40 : Without Motor & Bracket


Model	JMA-120	JMA-180
Surface Size	120 x 120mm	180 x 180mm
Travel Range	±5/ ±5/ ±5 °	±10/ ±10/ ±5 °
Travel Guide	Crossed-Roller guide , Cross Roller ring	
Resolution	2µm (Full step)	
Max. Speed	10mm/sec (based on 5phase motor)	
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)
Bi-Repeatability	± 2µm(C5) / ± 3µm(C7)	± 2µm(C5) / ± 3µm(C7)
Load Capacity	15 Kgf	30 Kgf
Parallelism	30µm	30µm
Driving Parallelism	20µm	20µm
Straightness	10µm	10µm
Weight	5Kg	13Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

**JMA**

C



**JMA-120**




**JMA-180**

## JMA-Series / Motorized Stage

**JMA****Model Selection**

1) 2) 3) 4)


**JMA-200-B5-O**

1) Axis : UVW- stage	2) Table Size 120 : 120x120mm 180 : 180x180mm 200 : 200x200mm 300 : 300x300mm OP : Make to Order	3) Grade of Ball Screw B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	4) Motor O 42 : Oriental Motor (5Phase) S 42 : Sanyo (2Phase) E 42 : Ezi-Servo Y 40 : Yaskawa Servo M 40 : Mitsubishi Servo X 40 : Without Motor & Bracket


Model	JMA-200	JMA-300
Surface Size	200 x 200mm	300 x 300mm
Travel Range	±5/ ±5/ ±2.5 °	±5/ ±5/ ±2.5 °
Travel Guide	Crossed-Roller guide , Cross Roller ring	
Resolution	2µm (Full step)	
Max. Speed	10mm/sec (based on 5phase motor)	
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)
Bi-Repeatability	± 2µm(C5) / ± 3µm(C7)	± 2µm(C5) / ± 3µm(C7)
Load Capacity	30 Kgf	40 Kgf
Parallelism	30µm	30µm
Driving Parallelism	20µm	20µm
Straightness	10µm	10µm
Weight	15Kg	20Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

# JMA

C



**JMA-200**




**JMA-300**

## JMU-Series / Motorized Stage

**JMU**

## Model Selection




1)      2)      3)      4)

**JMU-200-B5-O**




1) Axis	2) Table Size	3) Grade of Ball Screw	4) Motor
JMU : XYR- stage	100 : 100x100mm 120 : 120x120mm 150 : 150x150mm 200 : 200x200mm	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor ( 5Phase ) S : Sanyo ( 2Phase ) E : Ezi-Servo Y : Yaskawa Servo E 42 : Ezi-Servo X: Without Motor & Bracket

Model	JMU-100	JMU-120
Surface Size	100 x 100mm	120 x 120mm
Travel Range	±10/ ±10/ ±5 °	±10/ ±10/ ±5 °
Travel Guide	Crossed-Roller guide , Cross Roller ring	
Resolution	2μm (Full step)	
Max. Speed	10mm/sec (based on 5phase motor)	
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	7μm(C5) / 12μm(C7)	7μm(C5) / 12μm(C7)
Bi-Repeatability	± 2μm(C5) / ± 3μm(C7)	± 2μm(C5) / ± 3μm(C7)
Load Capacity	10 Kgf	12 Kgf
Parallelism	40μm	40μm
Driving Parallelism	20μm	20μm
Straightness	10μm	10μm
Weight	3.5Kg	4Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

# JMU



**JMU-100**




**JMU-120**

## JMU-Series / Motorized Stage

**JMU**

## Model Selection




1)      2)      3)      4)

**JMU-200-B5-O**




1) Axis	2) Table Size	3) Grade of Ball Screw	4) Motor
JMU : XYR-stage	100 : 100x100mm 120 : 120x120mm 150 : 150x150mm 200 : 200x200mm	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor ( 5Phase ) S : Sanyo ( 2Phase ) E : Ezi-Servo Y : Yaskawa Servo E 42 : Ezi-Servo X: Without Motor & Bracket

Model	JMU-150	JMU-200
Surface Size	150 x 150mm	200 x 200mm
Travel Range	±20/ ±20/ ±5 °	±20/ ±20/ ±4 °
Travel Guide	Crossed-Roller guide , Cross Roller ring	
Resolution	2μm (Full step)	
Max. Speed	10mm/sec (based on 5phase motor)	
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	7μm(C5) / 12μm(C7)	7μm(C5) / 12μm(C7)
Bi-Repeatability	± 2μm(C5) / ± 3μm(C7)	± 2μm(C5) / ± 3μm(C7)
Load Capacity	15 Kgf	25 Kgf
Parallelism	40μm	50μm
Driving Parallelism	20μm	20μm
Staingness	10μm	10μm
Weight	5.2Kg	7Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

# JMU



**JMU-150**



**JMU-200**

C

# Motorized Linear Stage



## Features of linear ball guide

### ■ Thin type

Machined guide structure eliminates the need fixing bolts. (Reduce 33% thickness, compared to conventional crossed roller stage).

### ■ High rigidity

Fewer fixing parts and stainless steel realize high rigidity with thin structure. (Load capacity is doubled compares to conventional crossed roller stage).

### ■ High accuracy

Machining the guide directly on housing increase driving performance and parallelism upper and lower surface. (Straightness is reduced to one-third and parallelism of motion is reduced to half).

### ■ Low price

Original production method significantly reduces cost. (Price is reduced by 30% or more compared to conventional crossed roller stage).

## Features of crossed roller stage

### ■ Light weight

Housing made of aluminum makes the stage lighter.

### ■ Compact

Crossed roller stage series more compact than conventional. (A photo sensor is embedded in the stage housing with few projections. You can use it without worrying about the operating position. High rigidity in spite of the thin body. A maximum load is 25kg).

### ■ High accuracy


The line contact between the roller and the V groove rail provides high rigidity high and an excellent low-friction micro feed with little operating slip.

C

## JMSX-Series / Motorized Stage

**JMSX****Model Selection**


1) 2) 3) 4) 5)

**JMSX-60L-B5-O**

1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMSX : X-stage JMSXY : XY-stage JMSZ : Z-stage with bracket JMSXYZ : XYZ stage	40 : 40x40mm 60 : 60x60mm	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor ( 5Phase ) S : Sanyo ( 2Phase ) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo


Model	JMSX-40	JMSX-60
Surface Size	40 x 40mm	60 x 60mm
Travel Range	14mm	20mm
Travel Guide	Linear guide	
Resolution	2µm (Full step)	
Max. Speed	10mm/sec (based on 5phase motor)	
Applicable Ball Screw	Ø6, lead 1(C5/C7)	Ø6, lead 1(C5/C7)
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)
Bi-Repeatability	± 1.5µm(C5) / ± 3µm(C7)	± 1.5µm(C5) / ± 3µm(C7)
Load Capacity	7 Kgf	10 Kgf
Parallelism	20µm	20µm
Driving Parallelism	10µm	10µm
Straightness	5µm	5µm
Weight	0.5Kg	0.7Kg
Material	Steel	
Finish Treatment	Electroless Nickel Plating	

# JMSX



C

**JMSX-40R**




**JMSX-60R**

## JMTX-Series / Motorized Stage

**JMTX****Model Selection**


1) 2) 3) 4)

**JMTX-6060-B5-O**

1) Axis	2) Surface Size	3) Grade of Ball Screw	4) Motor
JMTX : X-stage JMTXY : XY-stage JMTZ : Z-stage with bracket JMTXYZ : XYZ stage	6060 : 60x60mm 6070 : 60x70mm	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor ( 5Phase ) S : Sanyo ( 2Phase ) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo


Model	JMX-6060	JMTX-6060	JMTX-6070		
Surface Size	60 x 60mm	60 x 60mm	60 x 70mm		
Travel Range	20mm	20mm	30mm		
Travel Guide	Crossed-Roller guide	Linear guide			
Resolution	2µm (Full step)				
Max. Speed	10mm/sec (based on 5phase motor)				
Applicable Ball Screw	Ø6, lead 1(C5/C7)	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)		
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)		
Bi-Repeatability	± 1.5µm(C5) / ± 3µm(C7)	± 1.5µm(C5) / ± 3µm(C7)	± 1.5µm(C5) / ± 3µm(C7)		
Load Capacity	5 Kgf	10 Kgf	12 Kgf		
Parallelism	20µm	20µm	20µm		
Driving Parallelism	10µm	10µm	10µm		
Straightness	8µm	5µm	5µm		
Weight	0.45Kg	0.8Kg	1Kg		
Material	Aluminum	Steel	Steel		
Finish Treatment	Black Anodizing	Electroless Nickel Plating			

**JMTX**




**JMTX-6060**


**C**



**JMTX-6060**



**JMTX-6070**



## JMX-Series / Motorized Stage

**JMX**

## Model Selection



1) 2) 3) 4) 5)

**JMX - 60L - B5 - O**



1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMX : X-stage JMXY : XY-stage JMZ : Z-stage with bracket JMXYZ : XYZ stage	40 : 40x40mm 60 : 60x60mm 80 : 80x80mm 812 : 80x130mm 816 : 80x160mm	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor (5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo

Model	JMX-40	JMX-60
Surface Size	40 x 40mm	60 x 60mm
Travel Range	12mm	20mm
Travel Guide	Crossed-Roller guide	
Resolution	2µm (Full step)	
Max. Speed	10mm/sec (based on 5phase motor)	
Applicable Ball Screw	Ø6, lead 1(C5C7)	Ø8, lead 1(C5/C7)
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)
Bi-Repeatability	± 1.5µm(C5) / ± 3µm(C7)	± 1.5µm(C5) / ± 3µm(C7)
Load Capacity	3 Kgf	5 Kgf
Parallelism	20µm	20µm
Driving Parallelism	10µm	10µm
Straightness	5µm	8µm
Weight	0.3Kg	0.45Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

# JMX



**JMX-40R**




**JMX-60R**

## JMX-Series / Motorized Stage

**JMX**

## Model Selection


1) 2) 3) 4) 5)

**JMX - 60L - B5 - O**


1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMX : X-stage JMXY : XY-stage JMZ : Z-stage with bracket JMXYZ : XYZ stage	40 : 40x40mm 60 : 60x60mm 80 : 80x80mm 812 : 80x130mm 816 : 80x160mm	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor (5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo

Model	JMX-80	JMX-812	JMX-816
Surface Size	80 x 80mm	80 x 130mm	80 x 160mm
Travel Range	30mm	60mm	100mm
Travel Guide	Crossed-Roller guide		
Resolution	2µm (Full step)		
Max. Speed	10mm/sec (based on 5phase motor)		
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(or 2) (C5/C7)	Ø8, lead 1(or 2) (C5/C7)
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)	10µm(C5) / 15µm(C7)
Bi-Repeatability	± 1.5µm(C5) / ± 3µm (C7)	± 1.5µm(C5) / ± 3µm (C7)	± 1.5µm(C5) / ± 3µm (C7)
Load Capacity	10 Kgf	15 Kgf	18 Kgf
Parallelism	30µm	30µm	30µm
Driving Parallelism	15µm	15µm	15µm
Straightness	8µm	8µm	8µm
Weight	1.4Kg	1.8Kg	2.2Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JMX**



**JMX-80R**



**JMX-812R**



**JMX-816R**

**C**

# Motorized Z-Stage



## Features

### ■ Thin type

As Z axis having a direct moving X axis vertically supports load with the driving unit such as ballscrews, the horizontal plane Z axis stage supports the load with the wedge method crossed roller guides. It makes high rigidity and high tolerance.

### ■ High rigidity


The crossed roller is employed to the vertical guides, and improve the rigidity of rolling direction. (Highly reliable and good guides system).

### ■ Thin type

improves rolling direction rigidity and makes the body very thin.

## Wedge method crossed rollers

Place the V-groove rail and the crossed roller guide horizontally, diagonally, vertically in three okaces and moves up and down woth the precision ballscrew drive.



C

**JMHZ-Series / Motorized Stage****JMHZ****Model Selection**




1)            2)            3)            4)

**JMHZ - 60 - B5 - O**




1) Axis	2) Surface Size	3) Grade of Ball Screw	4) Motor
JMHZ : Horizontal Z-stage	60 : 60x88mm 80 : 80x100mm 120 : 120x120mm 200 : 200x200mm	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor(5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo

Model	JMHZ-60	JMHZ-80
Surface Size	60 x 88mm	80 x 100mm
Travel Range	4mm	8mm
Travel Guide	Crossed-Roller guide	
Resolution	0.25µm/pulse (Full step)	0.72µm/pulse (Full step)
Max. Speed	2.5mm/sec	3.6mm/sec
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	7µm(C5) / 12µm(C7)	7µm(C5) / 12µm(C7)
Bi-Repeatability	± 1.5µm(C5) / ± 3µm(C7)	± 1.5µm(C5) / ± 3µm(C7)
Load Capacity	5 Kgf	10 Kgf
Parallelism	30µm	30µm
Driving Parallelism	15µm	15µm
Straightness	10µm	10µm
Weight	1.2Kg	2Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

**JMHZ**



**JMHZ-60**



**JMHZ-80**

**C**

## JMHZ-Series / Motorized Stage

**JMHZ****Model Selection**

1)            2)            3)            4)


**JMHZ - 60 - B5 - O**

1) Axis	2) Surface Size	3) Grade of Ball Screw	4) Motor
JMHZ : Horizontal Z-stage	60 : 60x88mm 80 : 80x100mm 120 : 120x120mm 200 : 200x200mm	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor(5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo



Model	JMHZ-120	JMHZ-200
Surface Size	120 x 120mm	200 x 200mm
Travel Range	12mm	20mm
Travel Guide	Crossed-Roller guide	
Resolution	0.72μm/pulse (Full step)	3.6μm/pulse (Full step)
Max. Speed	3.6mm/sec	18mm/sec
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø12, lead 5(C5/C7)
Accuracy	7μm(C5) / 12μm(C7)	10μm(C5) / 15μm(C7)
Bi-Repeatability	± 1.5μm(C5) / ± 3μm(C7)	± 2μm(C5) / ± 4μm(C7)
Load Capacity	20 Kgf	25 Kgf
Parallelism	40μm	50μm
Driving Parallelism	20μm	20μm
Straightness	15μm	20μm
Weight	3.6Kg	5.2Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

**JMHZ**

C




**JMHZ-120**



**JMHZ-200**

# Motorized Rotary Stage


C




## Basis of selection

### ■ Ballscrew type

Sine motion stages make rolling movements. They are rarely worn and highly durable against repeated positioning at small angle.




To rotate the stage around  $\pm 5^\circ$ ,  $\pm 8^\circ$ ,  $\pm 15^\circ$  repeatedly.



Ballscrew type

## ■ Wedge method crossed rollers

Place the V-groove rail and the crossed roller guide horizontally, diagonally, vertically in three okaces and moves up and down woth the precision ballscrew drive.



## ■ Objects to be attached on upper and lower surface of the stage

Fixing an object with irregular surface to the stage or attaching the stage to an object with irregular surface may deform the stage surface and deteriorate the accuracy. [required flatness: 10 $\mu\text{m}$ ]

## ■ Stage attaching orientation


Specification of each product are those when installed on flat surface. Cautions are required for upside down, and vertical and horizontal mounting on side other than horizontal plane mounting.

Load capacity and accuracy significantly change by the mounting orientation.

## JMR-Series / Motorized Stage

**JMR****Model Selection**



1)      2)    3)    4)    5)

**JMR - 60L - B5 - O**


1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMR : Rotary-stage	60 : Ø60 80 : Ø80 100 : Ø89 120 : Ø120 150 : Ø140	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor (5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo

Model	JMR-60	JMR-80	JMR-100
Surface Size	Ø60	Ø80	Ø89
Travel Range	±5 °	±6 °	±8 °
Travel Guide	Thrust & Ball Bearing, Linerar Guide		
Resolution	2µm (Full step)		
Max. Speed	8.2 ° /sec (based on lead 1 Ball Screw)	5.9 ° /sec (based on lead 1 Ball Screw)	6.3 ° /sec (based on lead 1 Ball Screw)
Moving Distance /1 rotation	0.87 °	0.64 °	0.68 °
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	0.01 ° (C5) / 0.02 ° (C7)	0.01 ° (C5) / 0.02 ° (C7)	0.01 ° (C5) / 0.02 ° (C7)
Bi-Repeatability	± 0.0015 ° (C5) / ± 0.003 ° (C7)	± 0.0015 ° (C5) / ± 0.003 ° (C7)	± 0.0015 ° (C5) / ± 0.003 ° (C7)
Load Capacity	5 Kgf	8 Kgf	10 Kgf
Parallelism	30µm	40µm	50µm
Driving Parallelism	15µm	20µm	20µm
Straightness	10µm	15µm	20µm
Weight	1.6Kg	2Kg	2.2Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




# JMR






C



**JMR-60L**



**JMR-80L**




**JMR-100L**

## JMR-Series / Motorized Stage

**JMR****Model Selection**

1)      2)    3)    4)    5)



**JMR - 60L - B5 - O**

1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMR : Rotary-stage	60 : Ø60 80 : Ø80 100 : Ø89 120 : Ø120 150 : Ø140	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor (5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo



Model	JMR-120	JMR-150
Surface Size	Ø120	Ø140
Travel Range	±6 °	±15 °
Travel Guide	Thrust & Ball Bearing, Linerar Guide	
Resolution	2µm (Full step)	
Max. Speed	5.0 ° /sec (based on lead 1 Ball Screw)	4.8 ° /sec (based on lead 1 Ball Screw)
Moving Distance /1 rotation	0.55 °	0.53 °
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	0.01 ° (C5) / 0.02 ° (C7)	0.01 ° (C5) / 0.02 ° (C7)
Bi-Repeatability	± 0.0015 ° (C5) / ± 0.003 ° (C7)	± 0.0015 ° (C5) / ± 0.003 ° (C7)
Load Capacity	12 Kgf	20 Kgf
Parallelism	50µm	50µm
Driving Parallelism	20µm	20µm
Straightness	20µm	20µm
Weight	2.8Kg	3.0Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

# JMR

C



**JMR-120L**



**JMR-150L**

## JMG/JMT-Series / Motorized Stage

**JMG/JMT****Model Selection**

1)      2)      3)      4)      5)



**JMG-7070L-B5-O**

1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMG JMG2 JMT: Goniometer stage	7070 : 70x70mm 70101: 70x70mm 100 : 80x100mm	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor (5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo



Model	JMG-7070	JMG-70101
Surface Size	70 x 70mm	70 x 70mm
Work Distance	70mm±0.2mm	101mm±0.2mm
Rotation Center	70mm	101mm
Angular Range	±8° 1mm(0.744° )	±5° 1mm(0.5305° )
Travel Guide	Goniometer Crossed Roller Guide	
Resolution	0.003° (Full step)	
Max. Speed	7.6 ° /sec	5.6 ° /sec
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 1(C5/C7)
Accuracy	0.01 ° (C5) / 0.02 ° (C7)	0.01 ° (C5) / 0.02 ° (C7)
Bi-Repeatability	± 0.0015 ° (C5) / ± 0.003 ° (C7)	± 0.0015 ° (C5) / ± 0.003 ° (C7)
Load Capacity	5 Kgf	5 Kgf
Weight	0.8Kg	0.8Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

# JMG/JMT

C



JMG-7070R



JMG-70101R

## JMG/JMT-Series / Motorized Stage

**JMG/JMT****Model Selection**



1)      2)      3)      4)      5)

**JMG-7070L-B5-O**



1) Axis	2) Surface Size	3) Position of Sensor & Connector	4) Grade of Ball Screw	5) Motor
JMG JMG2 JMT: Goniometer stage	7070 : 70x70mm 70101: 70x70mm 100 : 80x100mm	L : Left from Motor R : Right from Motor	B5 : C5 Grade Ball Screw B7 : C7 Grade Ball Screw	O : Oriental Motor (5Phase) S : Sanyo (2Phase) E : Ezi-Servo Y : Yaskawa Servo M : Mitsubishi Servo

Model	JMG2-7070	JMT-100
Surface Size	70 x 70mm	80 x 100mm
Work Distance	TX : 101mm±0.2mm TY : 70mm±0.2mm	68mm±0.2mm
Rotation Center	TX : 101mm TY : 70mm	68mm
Angular Range	TX : ±5° 1mm(0.5305° ) TY : ±8° 1mm(0.744° )	±15° , 1mm(0.5208° )
Travel Guide	Goniometer Crossed Roller Guide	
Resolution	0.003° (Full step)	
Max. Speed	5.6 ° /sec	25 ° /sec
Applicable Ball Screw	Ø8, lead 1(C5/C7)	Ø8, lead 5(C7)
Accuracy	0.01 ° (C5) / 0.02 ° (C7)	0.02 ° (C7)
Bi-Repeatability	± 0.0015 ° (C5) / ± 0.003 ° (C7)	± 0.003 ° (C7)
Load Capacity	4.2 Kgf	5 Kgf
Weight	1.6 Kgf	1.9 Kgf
Material	Aluminum	
Finish Treatment	Black Anodizing	


# JMG/JMT




**JMG2-7070R**



**JMT-100**



# Motorized Stage



## **Manual Stage**



JCX-25/ JCXY-25

JCZ-25/ JCXYZ-25

JX-25/ JXY-25

JZ-25/ JXYZ-25

JCX-30/ JCXY-30

JCZ-30/ JCXYZ-30

JX-30/ JXY-30

JZ-30/ JXYZ-30

JCX-40(18H)/ JCX-40

JCXY-40/ JCXY-40-S

JCZ-40/ JCXYZ-40

JX-40/ JXY-40

JXY-40-S/ JZ-40

JXYZ-40

JX-5015/ JX-6025

JCX-60(18H)/ JCX-60

JCX-60(24H)/ JCXY-60

JCXY-60-S/ JCZ-60

JCXYZ-60/ JX-60

JXY-60/ JXY-60-S

JZ-60/ JXYZ-60

JCX-80-13/ JCX-80-25

JCXY-80-13/ JCXY-80-25

JCZ-80-13/ JCZ-80-25

JCXYZ-80-13/ JCXYZ-80-25

JCX-90(24H)/ JCXY-90(24H)

JCX-100-25/ JCX-100-50

JCXY-100-25/ JCXY-100-50

JCX-120-25/ JCX-120-50

JCXY-120-25/ JCXY-120-50

JCHZ 40/ 60/ 80/ 100/ 120

**JCX-Series(Aluminum Body)**



# JCX-25


**JCX-25L**

**JCX-25C**


**JCX-25R**


Model	JCX-25L	JCX-25R	JCX-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	1kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	10 $\mu$ m		
Weight	0.04 kg	0.04 kg	0.04 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JCX-25C(MIR)**
**JCX-25C**



D




**JCX-25L**



**JCX-25R**


**JCXY-Series(Aluminum Body)**



# JCXY-25

**JCXY-25L**

**JCXY-25C**



**JCXY-25R**


Model	JCXY-25L	JCXY-25R	JCXY-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	0.95kgf		
Parallelism	60 $\mu\text{m}$		
Driving Parallelism	20 $\mu\text{m}$		
Orthogonality	10 $\mu\text{m}$		
Weight	0.08 kg	0.08 kg	0.08 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-25C**



**JCXY-25L**



**JCXY-25R**

**JCZ-Series(Aluminum Body)**





# JCZ-25




**JCZ-25L**

**JCZ-25C**




**JCZ-25R**


Model	JCZ-25L	JCZ-25R	JCZ-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	0.5 kgf		
Parallelism	50 $\mu$ m		
Driving Parallelism	20 $\mu$ m		
Weight	0.06 kg	0.06 kg	0.06 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCZ-25C**



**JCZ-25L**





**JCZ-25R**




**JCXYZ-Series(Aluminum Body)**
**JCXYZ-25L JCXYZ-25C JCXYZ-25R**

# JCXYZ-25






Assembling Model	JCXYZ-25L	JCXYZ-25R	JCXYZ-25C
Orthogonality	JCXY-25L + JCZ-25L	JCXY-25R + JCZ-25R	JCXY-25C + JCZ-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed Roller Guide		
Load Capacity	0.5kgf		
Parallelism	$80\mu\text{m}$		
Driving Parallelism	$25\mu\text{m}$		
Weight	0.14 kg	0.14 kg	0.13 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXYZ-25C**



**JCXYZ-25L**





**JCXYZ-25R**

**JX-Series(Steel Body)**







# JX-25



Model	JX-25L	JX-25R	JX-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball guide		
Load Capacity	1.2 kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	10 $\mu$ m		
Weight	0.06 kg	0.06 kg	0.06 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JX-25C(MIR)**

**JX-25C**

D

**JX-25L****JX-25R**

**JX-Series(Steel Body)**


# JXY-25



**JXY-25L**

**JXY-25C**



**JXY-25R**


Model	JXY-25L	JXY-25R	JXY-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	1 kgf		
Parallelism	60 $\mu$ m		
Driving Parallelism	20 $\mu$ m		
Weight	0.12 kg	0.12 kg	0.12 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JXY-25C**



**JXY-25L**



**JXY-25R**

**JX-Series(Steel Body)**





# JZ-25

**JZ-25L**




**JZ-25C**

**JZ-25R**





Model	JZ-25L	JZ-25R	JZ-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	0.7kgf		
Parallelism	50 $\mu$ m		
Driving Parallelism	20 $\mu$ m		
Weight	0.08 kg	0.06 kg	0.08 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JZ-25C(MIR)**
**JZ-25C**

D




**JZ-25L**





**JZ-25R**



**JXYZ-Series(Steel Body)**

# JXYZ-25




**JXYZ-25L    JXYZ-25C    JXYZ-25R**


Assembling Model	JXYZ-25L	JXYZ-25R	JXYZ-25C
Orthogonality	JXY-25L + JZ-25L	JXY-25R + JZ-25R	JXY-25C + JZ-25C
Surface Size	25 x 25 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	0.7kgf		
Parallelism	$60\mu\text{m}$		
Driving Parallelism	$20\mu\text{m}$		
Weight	0.2 kg	0.2 kg	0.2 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JXYZ-25C**



**JXYZ-25L**





**JXYZ-25R**


**JCX-Series(Aluminum Body)**

# JCX-30




Model	JCX-30L	JCX-30R	JCX-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	1.2kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	10 $\mu$ m		
Weight	0.07 kg	0.07 kg	0.07 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCX-30C(MIR)**
**JCX-30C**



**JCX-30L**



**JCX-30R**

**JCXY-Series(Aluminum Body)**




# JCXY-30


**JCXY-30L**

**JCXY-30C**

**JCXY-30R**



Model	JCXY-30L	JCXY-30R	JCXY-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	1kgf		
Parallelism	60 $\mu\text{m}$		
Driving Parallelism	20 $\mu\text{m}$		
Orihogonality	10 $\mu\text{m}$		
Weight	0.14 kg	0.14 kg	0.14 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-30C**



**D**

**JCXY-30L**



**JCXY-30R**




**JCZ-Series(Aluminum Body)**


# JCZ-30

JCZ-30L    JCZ-30C    JCZ-30R




Model	JCZ-30L	JCZ-30R	JCZ-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	0.7kgf		
Parallelism	50 $\mu\text{m}$		
Driving Parallelism	20 $\mu\text{m}$		
Weight	0.09 kg	0.09 kg	0.09 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCZ-30C(MIR)**
**JCZ-30C**



JCZ-30L




JCZ-30R



JCXYZ-Series(Aluminum Body)

# JCXYZ-30


JCXYZ-30L JCXYZ-30C JCXYZ-30R




Model	JCXYZ-30L	JCXYZ-30R	JCXYZ-30C
Orthogonality	JCXY-30L + JCZ-30L	JCXY-30R + JCZ-30R	JCXY-30C + JCZ-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	0.7kgf		
Parallelism	80 $\mu\text{m}$		
Driving Parallelism	25 $\mu\text{m}$		
Weight	0.23 kg	0.23 kg	0.23 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		



**JCXYZ-30C**



**JCXYZ-30L**



**JCXYZ-30R**

**D**

**JX-Series(Steel Body)**

# JX-30

JX-30L







JX-30C




JX-30R




Model	JX-30L	JX-30R	JX-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	2kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	10 $\mu$ m		
Weight	0.12 kg	0.12 kg	0.12 kg
Material	Steel		
Finish Treatment	Electroless Ncikel Plating		

**JX-30C(MIR)****JX-30C**



D

**JX-30L**




**JX-30R**

**JXY-Series(Steel Body)**




# JXY-30






Model	JCXY-30L	JCXY-30R	JCXY-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	1.7kgf		
Parallelism	60 $\mu\text{m}$		
Driving Parallelism	20 $\mu\text{m}$		
Orihogonality	10 $\mu\text{m}$		
Weight	0.24 kg	0.24 kg	0.24 kg
Material	Steel		
Finish Treatment	Electroless Ncikel Plating		


**JXY-30C**

D




**JXY-30L**






**JXY-30R**


**JZ-Series(Steel Body)**

# JZ-30




Model	JZ-30L	JZ-30R	JZ-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	1.0kgf		
Parallelism	50 $\mu\text{m}$		
Driving Parallelism	20 $\mu\text{m}$		
Weight	0.14 kg	0.14 kg	0.14 kg
Material	Steel		
Finish Treatment	Electroless Ncikel Plating		


**JZ-30C(MIR)**
**JZ-30C**




D

JZ-30L







**JXYZ-Series(Steel Body)**

# JXYZ-30

**JXYZ-30C**
**JXYZ-30L**
**JXYZ-30R**





Model	JXYZ-30L	JXYZ-30R	JXYZ-30C
Orthogonality	JXY-30L + JZ-30L	JXY-30R + JZ-30R	JXY-30C + JZ-30C
Surface Size	30 x 30 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 3.25$ mm		
Minimum Reading of Micrometer	$1.0\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	1.0kgf		
Parallelism	$50\mu\text{m}$		
Driving Parallelism	$20\mu\text{m}$		
Weight	0.38 kg	0.38 kg	0.38 kg
Material	Steel		
Finish Treatment	Electroless Ncikel Plating		


**JXYZ-30C**



**D**

**JXYZ-30L**



**JXYZ-30R**



JCX-Series(Aluminum Body)

# JCX-40(18H)


JCX-40L(18H) JCX-40C(18H) JCX-40R(18H)






Model	JCX-40L(18H)	JCX-40R(18H)	JCX-40C(18H)
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	3kgf		
Parallelism	30 $\mu\text{m}$		
Driving Parallelism	10 $\mu\text{m}$		
Weight	0.13 kg	0.13 kg	0.12 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		






JCX-40C(18H)(MIR)



JCX-40C(18H)



**JCX-40L(18H)**



**JCX-40R(18H)**

**JCX-Series(Aluminum Body)**



# JCX-40

**JCX-40L**

**JCX-40C**


**JCX-40R**


Model	JCX-40L	JCX-40R	JCX-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	3kgf		
Parallelism	$30\mu\text{m}$		
Driving Parallelism	$10\mu\text{m}$		
Weight	0.14 kg	0.14 kg	0.14 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JCX-40C**

D



**JCX-40L**



**JCX-40R**

**JCXY-Series(Aluminum Body)**



# JCXY-40




**JCXY-40L**

**JCXY-40C**




**JCXY-40R**


Model	JCXY-40L	JCXY-40R	JCXY-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	2.8kgf		
Parallelism	$60\mu\text{m}$		
Driving Parallelism	$20\mu\text{m}$		
Orthogonality	$10\mu\text{m}$		
Weight	0.28 kg	0.28 kg	0.26 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-40C**



**JCXY-40L**



**JCXY-40R**

**D**

**Slim JCXY-Series(Aluminum Body)**

# JCXY-40-S

JCXY-40LS




JCXY-40RS





JCXY-40CS





Model	JCXY-40LS	JCXY-40RS	JCXY-40CS
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	2.8kgf		
Parallelism	$60\mu\text{m}$		
Driving Parallelism	$20\mu\text{m}$		
Orthogonality	$10\mu\text{m}$		
Weight	0.22 kg	0.22 kg	0.20 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		



**JCXY-40CS**



**JCXY-40LS**




**JCXY-40RS**

JCZ-Series(Aluminum Body)





# JCZ-40

JCZ-40L JCZ-40C

JCZ-40R





Model	JCZ-40L	JCZ-40R	JCZ-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	1.5kgf		
Parallelism	80 $\mu\text{m}$		
Driving Parallelism	30 $\mu\text{m}$		
Weight	0.21 kg	0.21 kg	0.20 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JCZ-40C(MIR)**

**JCZ-40C**





**JCZ-40LZ**


D



**JCZ-40L**




**JCZ-40RZ**





**JCZ-40R**



**JCXYZ-Series(Aluminum Body)**

# JCXYZ-40



**JCXYZ-40C**
**JCXYZ-40L**
**JCXYZ-40R**


Assembling Model	JCXYZ-40L	JCXYZ-40R	JCXYZ-40C
Orthogonality	JCXY-40L + JCZ-40L	JCXY-40R + JCZ-40R	JCXY-40C + JCZ-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed Roller Guide		
Load Capacity	1.5kgf		
Parallelism	$90\mu\text{m}$		
Driving Parallelism	$30\mu\text{m}$		
Weight	0.48 kg	0.48 kg	0.45 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXYZ-40C**



**JCXYZ-40L**



**JCXYZ-40R**

**JX-Series(Steel Body)**




# JX-40




**JX-40L**

**JX-40C**




**JX-40R**


Model	JX-40L	JX-40R	JX-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	7kgf		
Parallelism	$15\mu\text{m}$		
Driving Parallelism	$10\mu\text{m}$		
Weight	0.21 kg	0.21 kg	0.20 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JX-40C**



**JX-40L**



**JX-40R**

**D - 47**

**D**

**JXY-Series(Steel Body)**



# JXY-40


**JXY-40L**

**JXY-40C**


**JXY-40R**


Model	JXY-40L	JXY-40R	JXY-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	6.7kgf		
Parallelism	$30\mu\text{m}$		
Driving Parallelism	$15\mu\text{m}$		
Orthogonality	$10\mu\text{m}$		
Weight	0.42 kg	0.42 kg	0.42 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		




**JXY-40C**



D



**JXY-40L**



**JXY-40R**

**Slim JXY-Series(Steel Body)**

# JXY-40-S

JXY-40L-S





JXY-40C-S




JXY-40R-S





Model	JXY-40LS	JXY-40RS	JXY-40CS
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	7kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	15 $\mu$ m		
Orthogonality	10 $\mu$ m		
Weight	0.35 kg	0.35 kg	0.35 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		

**JXY-40CS**

D




**JXY-40LS**







**JXY-40RS**

**JZ-Series(Steel Body)**




# JZ-40



Model	JZ-40L	JZ-40R	JZ-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	3.5kgf		
Parallelism	40 $\mu\text{m}$		
Driving Parallelism	25 $\mu\text{m}$		
Weight	0.31 kg	0.31 kg	0.30 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		





**JZ-40C(MIR)**
**JZ-40C**

D



**JZ-40LZ**

**JZ-40L**




**JZ-40RZ**




**JZ-40R**




**JXYZ-Series(Steel Body)**

# JXYZ-40




**JXYZ-40C**
**JXYZ-40L**


Assembling Model	JXYZ-40L	JXYZ-40R	JXYZ-40C
Orthogonality	JXY-40L + JZ-40L	JXY-40R + JZ-40R	JXY-40C + JZ-40C
Surface Size	40 x 40 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	3.5kgf		
Parallelism	70 $\mu$ m		
Driving Parallelism	35 $\mu$ m		
Weight	0.73 kg	0.73 kg	0.72 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JXYZ-40C**




**JXYZ-40L**



**JXYZ-40R**


**JX50-Series(Steel Body)****JX-5015/ JX-6025**

D




Model	JX-5015	JX-6025
Surface Size	15 x 50 mm	25 x 60 mm
Position of Micrometer Head	Left	
Travel Range	$\pm 6.5\text{mm}$	
Minimum Reading of Micrometer	$10\mu\text{m}$	
Guide Type	Linear Ball Guide	
Load Capacity	3Kgf	5Kgf
Parallelism	$20\mu\text{m}$	
Driving Parallelism	$10\mu\text{m}$	
Weight	0.23Kg	0.3Kg
Material	Steel	
Finish Treatment	Electroless Nickel Plating	


D




**JX-5015(MIR)**



**JX-5015**



**JX-6025(MIR)**



**JX-6025**



**JCX-Series(Aluminum Body)**

# JCX-60(18H)




JCX-60L(18H)    JCX-60C(18H)    JCX-60R(18H)






Model	JCX-60L(18H)	JCX-60R(18H)	JCX-60C(18H)
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	6kgf		
Parallelism	$30\mu\text{m}$		
Driving Parallelism	$10\mu\text{m}$		
Weight	0.22 kg	0.22 kg	0.2 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCX-60C(18H)(MIR)**
**JCX-60C(18H)**

D



**JCX-60L(18H)**



**JCX-60R(18H)**

**JCX-Series(Aluminum Body)**




# JCX-60


**JCX-60L**

**JCX-60C**


**JCX-60R**


Model	JCX-60L	JCX-60R	JCX-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	6kgf		
Parallelism	$30\mu\text{m}$		
Driving Parallelism	$10\mu\text{m}$		
Weight	0.25 kg	0.25 kg	0.25 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCX-60C(MIR)**

**JCX-60C**



**JCX-60L**







**JCX-60R**

**JCX-Series(Aluminum Body)**



# JCX-60(24H)





Model	JCX-60L(24H)	JCX-60R(24H)	JCX-60C(24H)
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	6kgf		
Parallelism	$30\mu\text{m}$		
Driving Parallelism	$10\mu\text{m}$		
Weight	0.28 kg	0.28 kg	0.26 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCX-60C(24H)MIR**

**JCX-60C(24H)**

D



**JCX-60L(24H)**



**JCX-60R(24H)**

**JCXY-Series(Aluminum Body)**


# JCXY-60

**JCXY-60L**


**JCXY-60C**

**JCXY-60R**



Model	JCXY-60L	JCXY-60R	JCXY-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	5.7kgf		
Parallelism	60 $\mu$ m		
Driving Parallelism	20 $\mu$ m		
Orthogonality	10 $\mu$ m		
Weight	0.50 kg	0.50 kg	0.50 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-60C**

D



**JCXY-60L**



**JCXY-60R**

**Slim JCXY-Series(Aluminum Body)**



# JCXY-60-S


**JCXY-60LS**

**JCXY-60RS**


**JCXY-60CS**


Model	JCXY-60LS	JCXY-60RS	JCXY-60CS
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	5.7kgf		
Parallelism	60 $\mu$ m		
Driving Parallelism	20 $\mu$ m		
Orthogonality	10 $\mu$ m		
Weight	0.42 kg	0.42 kg	0.40 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-60CS**




**JCXY-60LS**






**JCXY-60RS**





**JCZ-Series(Aluminum Body)**

# JCZ-60





**JCZ-60C**


Model	JCZ-60L	JCZ-60R	JCZ-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	3kgf		
Parallelism	60 $\mu\text{m}$		
Driving Parallelism	30 $\mu\text{m}$		
Weight	0.40 kg	0.40 kg	0.39 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCZ-60C(MIR)**
**JCZ-60C**



**JCZ-60L**



**JCZ-60R**




D

**JCXYZ-Series(Aluminum Body)**




# JCXYZ-60

**JCXYZ-60C**
**JCXYZ-60L**
**JCXYZ-60R**





Assembling Model	JCXYZ-60L	JCXYZ-60R	JCXYZ-60C
Orthogonality	JCXY-60L + JCZ-60L	JCXY-60R + JCZ-60R	JCXY-60C + JCZ-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed Roller Guide		
Load Capacity	3kgf		
Parallelism	100 $\mu$ m		
Driving Parallelism	30 $\mu$ m		
Weight	0.90 kg	0.90 kg	0.87 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXYZ-60C**

D



**JCXYZ-60L**






**JCXYZ-60R**

**JX-Series(Steel Body)**




# JX-60






Model	JX-60L	JX-60R	JX-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	12kgf		
Parallelism	15 $\mu$ m		
Driving Parallelism	10 $\mu$ m		
Weight	0.43 kg	0.43 kg	0.42 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		



**JX-60C**




**JX-60L**




**JX-60R**

JXY-Series(Steel Body)

# JXY-60






Model	JXY-60L	JXY-60R	JXY-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	11.7kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	15 $\mu$ m		
Orthogonality	10 $\mu$ m		
Weight	0.86 kg	0.86 kg	0.86 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		






**JXY-60C**

D



**JXY-60L**




**JXY-60R**

**D - 75**




**Slim JXY-Series(Steel Body)**


# JXY-60-S

**JXY-60LS**

**JXY-60CS**


**JXY-60RS**


Model	JXY-60LS	JXY-60RS	JXY-60CS
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	12kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	15 $\mu$ m		
Orthogonality	10 $\mu$ m		
Weight	0.65 kg	0.65 kg	0.65 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		




**JXY-60CS**



D




**JXY-60LS**







**JXY-60RS**



**JZ-Series(Steel Body)**

# JZ-60

**JZ-60C**


Model	JZ-60L	JZ-60R	JZ-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Linear Ball Guide		
Load Capacity	6kgf		
Parallelism	50 $\mu\text{m}$		
Driving Parallelism	25 $\mu\text{m}$		
Weight	0.58 kg	0.58 kg	0.57 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		




**JZ-60C(MIR)**
**JZ-60C**



**JZ-60LZ**

D

**JZ-60L**




**JZ-60RZ**



**JZ-60R**




**JXYZ-Series(Steel Body)**

# JXYZ-60




**JXYZ-60C**
**JXYZ-60L**
**JXYZ-60R**


Assembling Model	JXYZ-60L	JXYZ-60R	JXYZ-60C
Orthogonality	JXY-60L + JZ-60L	JXY-60R + JZ-60R	JXY-60C + JZ-60C
Surface Size	60 x 60 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Linear Ball Guide		
Load Capacity	6kgf		
Parallelism	80 $\mu$ m		
Driving Parallelism	30 $\mu$ m		
Weight	1.44 kg	1.44 kg	1.42 kg
Material	Steel		
Finish Treatment	Electroless Nickel Plating		


**JXYZ-60C**



**JXYZ-60L**



**JXYZ-60R**

**JCX-Series(Aluminum Body)**





# JCX-80-13

**JCX-80L-13**


**JCX-80C-13**

**JCX-80R-13**


Model	JCX-80L-13	JCX-80R-13	JCX-80C-13
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	10kgf		
Parallelism	30 $\mu$ m		
Driving Parallelism	10 $\mu$ m		
Weight	0.40 kg	0.40 kg	0.39 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JCX-80C-13**



**JCX-80L-13A**

**JCX-80L-13**



**JCX-80R-13A**

**JCX-80R-13**

**D**

**JCX-Series(Aluminum Body)**

# JCX-80-25

JCX-80L-25





JCX-80R-25





JCX-80C-25





Model	JCX-80L-25	JCX-80R-25	JCX-80C-25
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	10kgf		
Parallelism	30 $\mu\text{m}$		
Driving Parallelism	10 $\mu\text{m}$		
Weight	0.41 kg	0.41 kg	0.41 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCX-80C-25(MIR)**
**JCX-80C-25**



**JCX-80L-25**



**JCX-80R-25**

## JCXY-Series(Aluminum Body)

**JCXY-80-13**


JCXY-80L-13

JCXY-80C-13




JCXY-80R-13






Model	JCXY-80L-13	JCXY-80R-13	JCXY-80C-13
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu$ m		
Guide Type	Crossed-Roller Guide		
Load Capacity	9.5kgf		
Parallelism	60 $\mu$ m		
Driving Parallelism	20 $\mu$ m		
Orthogonality	10 $\mu$ m		
Weight	0.80 kg	0.80 kg	0.78 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCXY-80C-13**

D



**JCXY-80L-13**



**JCXY-80R-13**

## JCXY-Series(Aluminum Body)

**JCXY-80-25**

JCXY-80L-25




JCXY-80R-25




JCXY-80C-25




Model	JCXY-80L-25	JCXY-80R-25	JCXY-80C-25
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5\text{mm}$		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	9.5kgf		
Parallelism	$60\mu\text{m}$		
Driving Parallelism	$20\mu\text{m}$		
Orthogonality	$10\mu\text{m}$		
Weight	0.82 kg	0.82 kg	0.82 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCXY-80C-25**



**JCXY-80L-25**



**JCXY-80R-25**

JCZ-Series(Aluminum Body)

# JCZ-80-13

JCZ-80C-13





JCZ-80L-13



JCZ-80R-13







Model	JCZ-80L-13	JCZ-80R-13	JCZ-80C-13
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	5kgf		
Parallelism	80 $\mu\text{m}$		
Driving Parallelism	30 $\mu\text{m}$		
Weight	0.68 kg	0.68 kg	0.67 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		







JCZ-80C-13(MIR)

JCZ-80C-13



**JCZ-80L-13**



**JCZ-80RZ-13**

**JCZ-80R-13**





D

**JCZ-Series(Aluminum Body)**


# JCZ-80-25

**JCZ-80C-25**
**JCZ-80L-25**
**JCZ-80R-25**



Model	JCZ-80L-25	JCZ-80R-25	JCZ-80C-25
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5$ mm		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	5kgf		
Parallelism	$80\mu\text{m}$		
Driving Parallelism	$30\mu\text{m}$		
Weight	0.69 kg	0.69 kg	0.69 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCZ-80C-25(MIR)**
**JCZ-80C-25**

D



**JCZ-80L-25**



**JCZ-80R-25**


## JCXYZ-Series(Aluminum Body)

**JCXYZ-80-13**


JCXYZ-80C-13


JCXYZ-80L-13

JCXYZ-80R-13




Assembling Model	JCXYZ-80L-13	JCXYZ-80R-13	JCXYZ-80C-13
Orthogonality	JCXY-80L-13 + JCZ-80L-13	JCXY-80R-13 + JCZ-80R-13	JCXY-80C-13 + JCZ-80C-13
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 6.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed Roller Guide		
Load Capacity	5.0kgf		
Parallelism	120 $\mu\text{m}$		
Driving Parallelism	40 $\mu\text{m}$		
Weight	1.48 kg	1.48 kg	1.45 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCXYZ-80C-13**



D

**JCXYZ-80L-13**



**JCXYZ-80R-13**


**D - 95**

JCXYZ-Series(Aluminum Body)


# JCXYZ-80-25

JCXYZ-80C-25


JCXYZ-80L-25




Assembling Model	JCXYZ-80L-25	JCXYZ-80R-25	JCXYZ-80C-25
Orthogonality	JCXYZ-80L-25 + JCZ-80L-25	JCXYZ-80R-25 + JCZ-80R-25	JCXYZ-80C-25 + JCZ-80C-25
Surface Size	80 x 80 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5$ mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed Roller Guide		
Load Capacity	5.0kgf		
Parallelism	120 $\mu\text{m}$		
Driving Parallelism	40 $\mu\text{m}$		
Weight	1.51 kg	1.51 kg	1.51 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		



**JCXYZ-80C-25**



**JCXYZ-80L-25**



**JCXYZ-80R-25**

**JCX-Series(Aluminum Body)**

# JCX-90(24H)





JCX-90L(24H)




JCX-90R(24H)

JCX-90C(24H)





Model	JCX-90L(24H)	JCX-90R(24H)	JCX-90C(24H)
Surface Size	90 x 90mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	15Kgf		
Parallelism	$30 \mu\text{m}$		
Driving Parallelism	$10 \mu\text{m}$		
Weight	0.7Kg	0.7Kg	0.7Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCX-90C(24H)(MIR)**

**JCX-90C(24H)**



**JCX-90L(24H)**



**JCX-90R(24H)**


## JCXY-Series(Aluminum Body)

**JCXY-90(24H)**




JCXY-90L-(24H) JCXY-90C(24H) JCXY-90R(24H)






Model	JCXY-90L(24H)	JCXY-90R(24H)	JCXY-90C(24H)
Surface Size	90 x 90mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	14.5Kgf		
Parallelism	$60 \mu\text{m}$		
Driving Parallelism	$20 \mu\text{m}$		
Weight	1.4Kg	1.4Kg	1.4Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCXY-90C(24H)**

D



**JCXY-90L(24H)**



**JCXY-90R(24H)**

**JCX-Series(Aluminum Body)**

# JCX-100-25

JCX-100L-25







JCX-100C-25




JCX-100R-25




Model	JCX-100L-25	JCX-100R-25	JCX-100C-25
Surface Size	100 x 100mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	15Kgf		
Parallelism	$60 \mu\text{m}$		
Driving Parallelism	$20 \mu\text{m}$		
Weight	1Kg	1Kg	1Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JCX-100C-25(MIR)**

**JCX-100C-25**



D



**JCX-100L-25**



**JCX-100R-25**

**D - 103**


JCX-Series(Aluminum Body)

# JCX-100-50




JCX-100L-50 JCX-100C-50 JCX-100R-50





Model	JCX-100L-50	JCX-100R-50	JCX-100C-50
Surface Size	100 x 100mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 25\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	15Kgf		
Parallelism	$60 \mu\text{m}$		
Driving Parallelism	$20 \mu\text{m}$		
Weight	1.2Kg	1.2Kg	1.15Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		



**JCX-100C-50**



**JCX-100L-50**



**JCX-100R-50**




**JCX-Series(Aluminum Body)**




# JCXY-100-25

JCXY-100L-25 JCXY-100C-25 JCXY-100R-25






Model	JCXY-100L-25	JCXY-100R-25	JCXY-100C-25
Surface Size	100 x 100mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	14Kgf		
Parallelism	$60 \mu\text{m}$		
Driving Parallelism	$20 \mu\text{m}$		
Weight	2.4Kg	2.4Kg	2.3Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-100C-25**



**JCXY-100L-25**



**JCXY-100R-25**

## JCX-Series(Aluminum Body)

**JCXY-100-50**

JCXY-100L-50




JCXY-100C-50





JCXY-100R-50





Model	JCXY-100L-50	JCXY-100R-50	JCXY-100C-50
Surface Size	100 x 100mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 25\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	14Kgf		
Parallelism	$60 \mu\text{m}$		
Driving Parallelism	$20 \mu\text{m}$		
Weight	2.4Kg	2.4Kg	2.3Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCXY-100C-50**



**JCXY-100L-50**




**JCXY-100R-50**

## JCX-Series(Aluminum Body)

**JCX-120-25**




JCXY-120L-25




JCXY-120R-25




Model	JCX-120L-25	JCX-120R-25	JCX-120C-25
Surface Size	120 x 120mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	±12.5mm		
Minimum Reading of Micrometer	10 $\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	20Kgf		
Parallelism	60 $\mu\text{m}$		
Driving Parallelism	20 $\mu\text{m}$		
Weight	1.30Kg	1.30Kg	1.26Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCX-120C-25**

D



**JCX-120L-25**




**JCX-120R-25**

JCX-Series(Aluminum Body)

# JCX-120-50




JCXY-120L-25




JCXY-120R-25




Model	JCX-120L-50	JCX-120R-50	JCX-120C-50
Surface Size	120 x 120mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 25\text{mm}$		
Minimum Reading of Micrometer	$10 \mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	20Kgf		
Parallelism	$60 \mu\text{m}$		
Driving Parallelism	$20 \mu\text{m}$		
Weight	1.5Kg	1.5Kg	1.45Kg
Material	Aluminum		
Finish Treatment	Black Anodizing		




**JCX-120C-50(MIR)**



**JCX-120C-50**



D

**JCX-120L-50****JCX-120R-50**


**JCXY-Series(Aluminum Body)**




# JCXY-120-25

**JCXY-120L-25**



**JCXY-120R-25**


Model	JCXY-120L-25	JCXY-120R-25	JCXY-120C-25
Surface Size	120 x 120 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 12.5\text{mm}$		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	18.5kgf		
Parallelism	$100\mu\text{m}$		
Driving Parallelism	$40\mu\text{m}$		
Orthogonality	$10\mu\text{m}$		
Weight	2.60 kg	2.60 kg	2.52 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCXY-120C-25**



**JCXY-120L-25**



**JCXY-120R-25**

## JCXY-Series(Aluminum Body)

**JCXY-120-50**



JCXY-120L-50





JCXY-120R-50





Model	JCXY-120L-50	JCXY-120R-50	JCXY-120C-50
Surface Size	120 x 120 mm		
Position of Micrometer Head	Left	Right	Center
Travel Range	$\pm 25\text{mm}$		
Minimum Reading of Micrometer	$10\mu\text{m}$		
Guide Type	Crossed-Roller Guide		
Load Capacity	18.5kgf		
Parallelism	$100\mu\text{m}$		
Driving Parallelism	$40\mu\text{m}$		
Orthogonality	$10\mu\text{m}$		
Weight	3.0 kg	3.0 kg	2.9 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		

**JCXY-120C-50**



**JCXY-120C-50**



**JCXY-120R-50**

**JCHZ-Series(Aluminum Body)**

# JCHZ- 40/60/80




JCHZ-60


JCHZ-40

JCHZ-80





Model	JCHZ-40	JCHZ-60	JCHZ-80
Surface Size	40 x 40 mm	60 x 60 mm	80 x 80 mm
Position of Micrometer Head	Center		
Travel Range	±3.0 mm	±5.0 mm	±5.0 mm
Minimum Reading of Micrometer	10µm		
Guide Type	Crossed-Roller Guide		
Load Capacity	3kgf	5kgf	5kgf
Parallelism	60µm	65µm	80µm
Driving Parallelism	25µm	25µm	30µm
Weight	0.15 kg	0.45 kg	0.55 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JCHZ-40**



D

**JCHZ-60**




**JCHZ-80**


JCHZ-Series(Aluminum Body)

# JCHZ-100 / 120

JCHZ-100




JCHZ-120




D

Model	JCHZ-100	JCHZ-120
Surface Size	100 x 100 mm	120 x 120 mm
Position of Micrometer Head	Center	
Travel Range	±5 mm	±5 mm
Minimum Reading of Micrometer	10 $\mu$ m	
Guide Type	Crossed-Roller Guide	
Load Capacity	8kgf	8kgf
Parallelism	100 $\mu$ m	100 $\mu$ m
Driving Parallelism	30 $\mu$ m	30 $\mu$ m
Weight	1 kg	1.2 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	



D

**JCHZ-100**




**JCHZ-120**

# S stage

---

D



# **Goniometer Stage**



**JT-Series**

**JT-40**

**JT-60**

**JT-8087**

**E**

**JT-Series(Aluminum)**




# JT-40




**JT1-4015**

**JT1-4035**




**JT2-4015**


Model	JT1-4015	JT1-4035	JT2-4015
Surface Size	40 x 40 mm		
Rotation Center	15 mm	35 mm	15 mm
Travel Range	$\pm 20^\circ$	$\pm 20^\circ$	TX : $\pm 20^\circ$ , Ty : $\pm 20^\circ$
Minimum Reading of Vernier	0.1° / Vernier		
Rotation Angle	$\approx 3.53^\circ$	$\approx 2.19^\circ$	TX : $\approx 3.53^\circ$ , Ty : $\approx 2.19^\circ$
Travel Guide	Dovetail, Worm & Gear		
Load Capacity	3.0kgf		2.5kgf
Weight	0.25 kg	0.24 kg	0.5 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		


**JT1-4015L**

**JT1-4015R**



JT1-4035R






JT2-4015R

**JT-Series(Aluminum)**



# JT-40



Model	JT1-4035	JT1-4051	JT2-4035
Surface Size	40 x 40 mm		
Rotation Center	35 mm	51 mm	35 mm
Travel Range	$\pm 20^\circ$	$\pm 15^\circ$	TX : $\pm 15^\circ$ , TY : $\pm 20^\circ$
Minimum Reading of Vernier	$0.1^\circ$ / Vernier		
Rotation Angle	$\approx 2.19^\circ$	$\approx 1.60^\circ$	TX : $\approx 1.60^\circ$ , TY : $\approx 2.19^\circ$
Travel Guide	Dovetail, Worm & Gear		
Load Capacity	3.0kgf		2.8kgf
Weight	0.24 kg	0.22 kg	0.46 kg
Material	Aluminum		
Finish Treatment	Black Anodizing		





**JT1-4035L**
**JT1-4035R**

## Goniometer Stage



**JT1-4051R**

E



**JT2-4035L**

**JT2-4035R**




**E - 5**

**JT-Series(Aluminum)**




# JT-60

**JT1-6060**
**JT1-6080**
**JT2-6060**


Model	JT1-6060	JT1-6080	JT2-6060
Surface Size	60 x 60 mm		
Rotation Center	60 mm	80 mm	60 mm
Travel Range	$\pm 15^\circ$	$\pm 10^\circ$	TX : $\pm 10^\circ$ , Ty : $\pm 15^\circ$
Minimum Reading of Vernier	$0.1^\circ$ / Vernier		
Rotation Angle	$\approx 1.30^\circ$	$\approx 1.00^\circ$	TX : $\approx 1.00^\circ$ , Ty : $\approx 1.30^\circ$
Travel Guide	Dovetail, Worm & Gear		
Load Capacity	5.0kgf	4.8 kgf	
Weight	0.25 kg	0.50 kg	
Material	Aluminum		
Finish Treatment	Black Anodizing		





**JT1-6060L**
**JT1-6060R**

## Goniometer Stage



**JT1-6080L**

**JT1-6080R**



**JT2-6060L**

**JT2-6060R**

E


JT-Series(Aluminum)

# JT-8087

JT-8087L





JT-8087R





E

Model	JT-8087L	JT-8087R
Surface Size	80 x 80 mm	
Rotation Center	87 mm	
Travel Range	±15°	
Minimum Reading of Vernier	0.1° / Vernier	
Rotation Angle	≈0.9°	
Travel Guide	Dovetail, Worm & Gear	
Load Capacity	8 kgf	
Weight	0.53 kg	
Material	Aluminum	
Finish Treatment	Black Anodizing	




**JT-8087L**



**JT-8087R**

# S<sub>tage</sub>

---



E

*Goniometer*

# **Rotary Stage**



## **JCR Series**

**JCR-40**

**JCR-60**

**JCR-80**

**JCR-100**

**JCR-120**

**JCRF-80**


**JCRT-60**

**JCRT-100**

**F**




JCR-Series(Aluminum)

# JCR-40






F

Model	JCR-40L	JCR-40R
Surface Size	$\phi$ 40	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\phi$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu\text{m}$	
Readable Resolution	2°	
Load Capacity	1.0kgf	
Parallelism	30 $\mu\text{m}$	
Rotational Concentricity	30 $\mu\text{m}$	
Weight	0.09 kg	0.09 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	




**JCR-40L**



**JCR-40R**




JCR-Series(Aluminum)

# JCR-60






F

Model	JCR-60L	JCR-60R
Surface Size	$\phi$ 60	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\phi$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu\text{m}$	
Readable Resolution	1°	
Load Capacity	3.0kgf	
Parallelism	50 $\mu\text{m}$	
Rotational Concentricity	50 $\mu\text{m}$	
Weight	0.28 kg	0.28 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	




**JCR-60L**



**JCR-60R**



JCR-Series(Aluminum)

# JCR-80





F

Model	JCR-80L	JCR-80R
Surface Size	$\phi$ 80	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\phi$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu$ m	
Readable Resolution	1°	
Load Capacity	4.0kgf	
Parallelism	50 $\mu$ m	
Rotational Concentricity	50 $\mu$ m	
Weight	0.45 kg	0.45 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	




**JCR-80L**



**JCR-80R**



JCR-Series(Aluminum)

# JCR-100





F

Model	JCR-100L	JCR-100R
Surface Size	$\phi$ 100	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\phi$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu$ m	
Readable Resolution	1°	
Load Capacity	5.0kgf	
Parallelism	60 $\mu$ m	
Rotational Concentricity	50 $\mu$ m	
Weight	0.8 kg	0.8 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	




**JCR-100L**



**JCR-100R**



JCR-Series(Aluminum)

# JCR-120





F

Model	JCR-120L	JCR-120R
Surface Size	$\phi$ 120	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\phi$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu$ m	
Readable Resolution	1°	
Load Capacity	6.0 kgf	
Parallelism	80 $\mu$ m	
Rotational Concentricity	60 $\mu$ m	
Weight	1 kg	1 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	



**JCR-120L**



**JCR-120R**


JCRF-Series(Aluminum)

# JCRF - 80




F

Model	JCRF-80L	JCRF-80R
Surface Size	$\varnothing$ 80	
Position of Micrometer Head	Left	Right
Travel Range	$\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu\text{m}$	
Readable Resolution	1°	
Load Capacity	10kgf	
Parallelism	50 $\mu\text{m}$	
Rotational Concentricity	50 $\mu\text{m}$	
Weight	0.5 kg	0.5 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	



**JCRF-80L**

F




**JCRF-80R**





JCRT-Series(Aluminum)

# JCRT - 60






F

Model	JCRT-60L	JCRT-60R
Surface Size	$\varnothing$ 60	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\varnothing$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu\text{m}$	
Readable Resolution	1°	
Load Capacity	8.0kgf	
Parallelism	30 $\mu\text{m}$	
Rotational Concentricity	30 $\mu\text{m}$	
Weight	0.5 kg	0.5 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	



F

**JCRT-60L**




**JCRT-60R**

**F - 15**


JCRT-Series(Aluminum)

# JCRT - 100




F


Model	JCRT-100L	JCRT-100R
Surface Size	$\varnothing$ 100	
Position of Micrometer Head	Left	Right
Travel Range	Coarse : $\varnothing$ 360° Fine : $\pm 5^\circ$	
Minimum Reading of Micrometer	10 $\mu\text{m}$	
Readable Resolution	1°	
Load Capacity	10.0kgf	
Parallelism	50 $\mu\text{m}$	
Rotational Concentricity	50 $\mu\text{m}$	
Weight	0.7 kg	0.7 kg
Material	Aluminum	
Finish Treatment	Black Anodizing	




**JCRT-100L**



**JCRT-100R**



# Rotary Stage





## Multi Stage



JA4-80 / JA5-80



G

## Multi-Series



**JA4-80 / JA5-80**

Model	JA4-80	JA5-80
Surface Size	80 x 80 mm	Ø80
Travel Range	X : ±5mm TX:±3° Y : ±5mm TX:±3° R : ±5 °	X : ±5mm TX:±3° Y : ±5mm TX:±3° R : ±5 °
Travel Guide	Guide Pin, Spring Interlock	Guide Pin, Spring Interlock
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	80µm	100µm
Driving Parallelism	30µm	30µm
Load Capacity	6 kgf	6 kgf
Weight	0.8kg	1.3kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

# JD4-80 / JD5-80




**JA4-80**




**JA5-80**

**G**



# Multi Stage



## **Motorized Stage (Screw Type)**




### Screw Type

JLD  
JD-25S  
JD-243S  
JD2-311S  
JD2-317SS  
JD1-312S  
JD1-310S  
JD-43S  
JD-44S  
JD-48S  
JD-55S  
JD-60S  
JD-66S


### Rack & Pinion Type

JD-246P  
JD-249P  
JD-2411P  
JD3-255P  
JD3-257P  
JD-40P  
JD-44P  
JD-46P  
JD-48P  
JD-49P  
JD-414P  
JD-419P


**Dovetail Screw Series****JLD**

Model	JLD-ST50	JLD-ST100
Upper Surface Size	60 x 60mm	60 x 60mm
Travel Range	50mm	100mm
Travel Guide	Dovetail, Screw	
Lead Screw	$\varnothing 10$ , Lead 1.5	
Parallelism	$50\mu\text{m}$	
Driving Parallelism	$60\mu\text{m}$	$100\mu\text{m}$
Load capacity	2.5Kgf	2.5Kgf
Weight	0.74 Kg	0.89 Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	


## Dovetail Stage (screw type)




**JLD-ST50**



**JLD-ST50(MIR)**




**JLD-ST100**





**JLD-ST100(MIR)**

H


**Dovetail Screw Series****JLD**

Model	JLD-ST150	JLD-ST200
Upper Surface Size	60 x 60mm	60 x 60mm
Travel Range	150mm	200mm
Travel Guide	Dovetail, Screw	
Lead Screw	Ø10, Lead 1.5	
Parallelism	50µm	
Driving Parallelism	100µm	100µm
Load capacity	2.5Kgf	2.5Kgf
Weight	1.04 Kg	1.19 Kg
Material	Aluminum	
Finish Treatment	Black Anodizing	



## Dovetail Stage (screw type)




**JLD-ST150**



**JLD-ST150(MIR)**



**JLD-ST200**




**JLD-ST200(MIR)**




H

## Dovetail Screw Series

# JD-25S






Model	JD1-25S	JD2-25S	JD3-25S	JD4-25S
Surface Size	25 x 25 mm			
Travel Range	±4 mm	±4 mm	±4 mm	±4 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier	0.1mm / Vernier	0.1mm / Vernier
Parallelism	30µm	50µm	40µm	50µm
Driving Parallelism	30µm	30µm	30µm	30µm
Load Capacity	1.0kgf	0.8kgf	0.5kgf	0.5kgf
Base Plate	X	X	X	X
Weight	0.1kg	0.2kg	0.12kg	0.32kg
Material	Aluminum	Aluminum	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing	Black Anodizing	Black Anodizing




**JD1-25S**

## Dovetail Stage (screw type)






## Dovetail Screw Series

# JD-243S



Model	JD1-243S	JD2-243S
Surface Size	24 x 30 mm	24 x 30 mm
Travel Range	±5 mm	±5 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	30µm	50µm
Driving Parallelism	30µm	30µm
Load Capacity	1.0kgf	0.8kgf
Base Plate	X	X
Weight	0.12kg	0.24kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing




## Dovetail Stage (screw type)



**JD1-243S(MIR)**


**JD1-243S**

H




**JD2-243S**

## Dovetail Screw Series

**JD2-311S / JD2-317SS**


Model	JD2-311S(Bi-Directional)	JD2-317SS(Bi-Directional)
Upper Surface Size	20 x 30mm	20 x 30mm
Travel Range	L25mm, R25mm	L55mm, R55mm
Travel Guide	Dovetail, Screw	
Readable Resolution	0.1mm / Vernier	
Parallelism	40µm	
Driving Parallelism	30µm	
Load capacity	2Kgf	
Weight	0.3 Kg	
Material	Aluminum	
Finish Treatment	Black Anodizing	

## Dovetail Stage (screw type)



**JD2-311S(MIR)**

**JD2-311S**




**JD2-317SS(MIR)**

**JD2-317SS**


H

## Dovetail Screw Series

**JD1-312S/ JD1-310S****H**


Model	JD1-312S	JD1-310S
Upper Surface Size	20 x 30mm	20 x 30mm
Travel Range	70mm	50mm
Travel Guide	Dovetail, Screw	
Readable Resolution	0.1mm / Vernier	
Parallelism	40µm	
Driving Parallelism	30µm	
Load capacity	2Kgf	
Weight	0.3 Kg	
Material	Aluminum	
Finish Treatment	Black Anodizing	

## Dovetail Stage (screw type)



**JD1-312S(MIR)**

**JD1-312S**




**JD1-310S(MIR)**

**JD1-310S**

H





**Dovetail Screw Series**

# JD-43S






Model	JD1-43S	JD2-43S
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	40µm	60µm
Driving Parallelism	30µm	30µm
Load Capacity	2.5kgf	2.2kgf
Base Plate	X	X
Weight	0.18kg	0.36kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD1-43S(MIR)**

**JD1-43S**




**JD2-43S**

H


**Dovetail Screw Series**

# **JD-43S**




Model	JD3-43S	JD4-43S
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	120µm
Driving Parallelism	30µm	30µm
Load Capacity	1.2kgf	1.2kgf
Base Plate	X	X
Weight	0.2kg	0.56kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD3-43S**


H



**JD4-43S**




**Dovetail Screw Series**

# **JD-44S**





Model	JD1-44S	JD2-44S
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	40µm	60µm
Driving Parallelism	30µm	30µm
Load Capacity	2.0kgf	1.8kgf
Base Plate	X	X
Weight	0.15kg	0.3kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD1-44S**




**JD2-44S**

H


**Dovetail Screw Series**

# JD-44S




Model	JD3-44S	JD4-44S
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	120µm
Driving Parallelism	30µm	30µm
Load Capacity	1.0kgf	1.0kgf
Base Plate	X	X
Weight	0.17kg	0.47kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)




**JD3-44S**



**JD4-44S**




Dovetail Screw Series

# JD-48S





Model	JD1-48S	JD2-48S
Surface Size	40 x 80 mm	40 x 80 mm
Travel Range	±25 mm	±25 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	40µm	60µm
Driving Parallelism	30µm	30µm
Load Capacity	4.0kgf	3.7kgf
Base Plate	X	X
Weight	0.2kg	0.4kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD1-48S(MIR)**

**JD1-48S**




**JD2-48S**

H






**Dovetail Screw Series**

# JD-55S







Model	JD1-55S	JD2-55S
Surface Size	50 x 50 mm	50 x 50 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	70µm
Driving Parallelism	30µm	30µm
Load Capacity	3.5kgf	3.2kgf
Base Plate	X	X
Weight	0.22kg	0.44kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD1-55S**




H

**JD2-55S**


**Dovetail Screw Series**

# JD-55S





Model	JD3-55S	JD4-55S
Surface Size	50 x 50 mm	50 x 50 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Screw + Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	60µm	130µm
Driving Parallelism	30µm	30µm
Load Capacity	1.8kgf	1.8kgf
Base Plate	X	X
Weight	0.24kg	0.68kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD3-55S**




**JD4-55S**

**H**





**Dovetail Screw Series**

# JD-60S






Model	JD1-60S	JD2-60S
Surface Size	60 x 60 mm	60 x 60 mm
Travel Range	±15 mm	±15 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	70µm
Driving Parallelism	30µm	30µm
Load Capacity	3.0kgf	2.8kgf
Base Plate	X	X
Weight	0.2kg	0.4kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD1-60S(MIR)**

**JD1-60S**





**JD2-60S**

H




Dovetail Screw Series

# JD-60S






Model	JD3-60S	JD4-60S
Surface Size	60 x 60 mm	60 x 60 mm
Travel Range	± 15 mm	± 15 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	60µm	130µm
Driving Parallelism	30µm	30µm
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	X
Weight	0.22kg	0.62kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)




**JD3-60S**



**JD4-60S**





**Dovetail Screw Series**

# JD-66S







Model	JD1-66S	JD2-66S
Surface Size	60 x 60 mm	60 x 60 mm
Travel Range	±15 mm	±15 mm
Travel Guide	Dovetail , Screw	Dovetail , Screw
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	70µm
Driving Parallelism	30µm	30µm
Load Capacity	4.0kgf	3.7kgf
Base Plate	X	X
Weight	0.3kg	0.6kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (screw type)



**JD1-66S(MIR)**

**JD1-66S**



**JD2-66S**


**Dovetail Screw Series**

# JD-66S





Model	JD3-66S	JD4-66S
Surface Size	60 x 60 mm	60 x 60 mm
Travel Range	±15 mm	±15 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Screw + Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	60µm	130µm
Driving Parallelism	30µm	30µm
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	X
Weight	0.33kg	0.93kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing




## Dovetail Stage (screw type)



**JD3-66S**



**JD4-66S**



H

## **Motorized Stage (Rack & Pinion Type)**



### **Dovetail Rack & Pinion\_Series**

JD-246P/ JD-249P/ JD-2411P

JD3-255P/ JD3-257P

JD-40P

JD-44P

JD-46P

JD-48P

JD-49P


JD-414P

JD-419P


JDHZ-40/ JDHZ-60

**Dovetail Rack & Pinion-Series**


# **JD-246P, 249P, 2411P**




Model	JD1-246P	JD1-249P	JD1-2411P
Surface Size	24 x 60 mm	24 x 90 mm	24 x 110 mm
Travel Range	±20 mm	±30 mm	±40 mm
Travel Guide	Dovetail , Rack & Pinion		
Readable Resolution	0.1mm / Vernier		
Parallelism	40µm		
Driving Parallelism	30µm		
Load Capacity	1.0kgf	1.5kgf	2.0kgf
Base Plate	X		
Weight	0.1kg	0.15kg	0.2kg
Material	Aluminum	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing	Black Anodizing


**JD1-246P**

## Dovetail Stage (Rack & Pinion type)




**JD1-249P**



**JD1-2411P**


**Dovetail Rack & Pinion-Series**

# **JD3-255P/ JD3-257P**




Model	JD3-255P	JD3-257P
Surface Size	25 x 50 mm	25 x 70 mm
Travel Range	±15 mm	±25 mm
Travel Guide	Dovetail , Rack & Pinion	
Readable Resolution	0.1mm / Vernier	
Parallelism	40µm	
Driving Parallelism	30µm	
Load Capacity	0.120kgf	0.135kgf
Base Plate	X	
Weight	0.12kg	0.13kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

## Dovetail Stage (Rack & Pinion type)




**JD3-255P**



**JD3-257P**


**Dovetail Rack & Pinion-Series**

# **JD-40P**




Model	JD1-40P	JD2-40P
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	40µm	70µm
Driving Parallelism	30µm	30µm
Load Capacity	2.5kgf	2.3kgf
Base Plate	X	X
Weight	0.15kg	0.3kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)




**JD1-40P**



**JD2-40P**


**Dovetail Rack & Pinion-Series**

# JD-40P




Model	JD3-40P	JD4-40P
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	120µm
Driving Parallelism	30µm	30µm
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	X
Weight	0.17kg	0.47kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD3-40P**



**JD4-40P**


**Dovetail Rack & Pinion-Series**

# JD-44P




Model	JD1-44P	JD2-44P
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	40µm	70µm
Driving Parallelism	30µm	30µm
Load Capacity	2.5kgf	2.3kgf
Base Plate	X	X
Weight	0.15kg	0.3kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD1-44P**



**JD2-44P**


**Dovetail Rack & Pinion-Series**

# **JD-44P**




Model	JD3-44P	JD4-44P
Surface Size	40 x 40 mm	40 x 40 mm
Travel Range	±10 mm	±10 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail, Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	120µm
Driving Parallelism	30µm	30µm
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	X
Weight	0.17kg	0.47kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD3-44P**



**JD4-44P**



Dovetail Rack & Pinion-Series

# JD-46P





Model	JD1-46P	JD2-46P
Surface Size	40 x 60 mm	40 x 60 mm
Travel Range	±20 mm	±20 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	40µm	70µm
Driving Parallelism	30µm	30µm
Load Capacity	3kgf	2.7kgf
Base Plate	O	O
Weight	0.28kg	0.56kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)




**JD1-46P**



**JD2-46P**




**Dovetail Rack & Pinion-Series**

# **JD-46P**






Model	JD3-46P	JD4-46P
Surface Size	40 x 60 mm	40 x 60 mm
Travel Range	±20 mm	±20 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail, Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	120µm
Driving Parallelism	30µm	30µm
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	O
Weight	0.3kg	0.86kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD3-46P**



**JD4-46P**





**Dovetail Rack & Pinion-Series**

# **JD-48P**







Model	JD1-48P	JD2-48P
Surface Size	40 x 80 mm	40 x 80 mm
Travel Range	±25 mm	±25 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	80µm
Driving Parallelism	30µm	30µm
Load Capacity	3.8kgf	3.5kgf
Base Plate	0	0
Weight	0.34kg	0.68kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD1-48P**



**JD2-48P**


**Dovetail Rack & Pinion-Series**

# JD-48P




Model	JD3-48P	JD4-48P
Surface Size	40 x 80 mm	40 x 80 mm
Travel Range	±25 mm	±25 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail, Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	60 $\mu$ m	130 $\mu$ m
Driving Parallelism	30 $\mu$ m	30 $\mu$ m
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	O
Weight	0.36kg	1.04kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)




**JD3-48P**



**JD4-48P**





**Dovetail Rack & Pinion-Series**

# JD-49P







Model	JD1-49P	JD2-49P
Surface Size	40 x 90 mm	40 x 90 mm
Travel Range	±30 mm	±30 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	50µm	80µm
Driving Parallelism	30µm	30µm
Load Capacity	4kgf	3.7kgf
Base Plate	O	O
Weight	0.36kg	0.72kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)




**JD1-49P**



**JD2-49P**


Dovetail Rack & Pinion-Series

# JD-49P




Model	JD3-49P	JD4-49P
Surface Size	40 x 90 mm	40 x 90 mm
Travel Range	±30 mm	±30 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail, Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	60µm	130µm
Driving Parallelism	30µm	30µm
Load Capacity	1.5kgf	1.5kgf
Base Plate	X	O
Weight	0.38kg	1.1kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD3-49P**



**JD4-49P**




**Dovetail Rack & Pinion-Series**

# **JD-414P**







Model	JD1-414P	JD2-414P
Surface Size	40 x 140 mm	40 x 140 mm
Travel Range	±50 mm	±50 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	80µm	100µm
Driving Parallelism	30µm	30µm
Load Capacity	4.5kgf	4.3kgf
Base Plate	O	O
Weight	0.55kg	1.1kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)



**JD1-414P**



**JD2-414P**


**Dovetail Rack & Pinion-Series**

# **JD-419P**




Model	JD1-419P	JD2-419P
Surface Size	40 x 190 mm	40 x 190 mm
Travel Range	±80 mm	±80 mm
Travel Guide	Dovetail , Rack & Pinion	Dovetail , Rack & Pinion
Readable Resolution	0.1mm / Vernier	0.1mm / Vernier
Parallelism	100µm	140µm
Driving Parallelism	30µm	30µm
Load Capacity	5kgf	4.7kgf
Base Plate	O	O
Weight	1kg	2kg
Material	Aluminum	Aluminum
Finish Treatment	Black Anodizing	Black Anodizing

## Dovetail Stage (Rack & Pinion type)




**JD1-419P**



**JD2-419P**




Dovetail Rack & Pinion-Series

# JDHZ-40 / 60






Model	JDHZ-40	JDHZ-60
Surface Size	40 x 40 mm	60 x 60 mm
Position of Micrometer Head	Center	
Travel Range	±5 mm	±10 mm
Travel Guide	Dovetail , Rack & Pinion	
Readable Resolution	0.1mm / Vernier	
Load Capacity	1.0 kgf	1.5 kgf
Parallelism	40µm	40µm
Driving Parallelism	30µm	30µm
Load Capacity	1.0kgf	1.5kgf
Weight	0.13kg	0.47kg
Material	Aluminum	
Finish Treatment	Black Anodizing	

## Dovetail Stage (Rack & Pinion type)




**JDHZ-40**




**JDHZ-60**

## Dovetail Rack &amp; Pinion-Series



## **Micrometer Head**



JALB71 / JALB72

JALB73 / JALB74


JALB73-DIG

**J**


# JALB-71




JALB-71-R	
유효피치 Stroke	$\pm 3.25\text{mm}$
눈금단위 Minimum Reading	10 $\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Round




JALB-71-F	
유효피치 Stroke	$\pm 3.25\text{mm}$
눈금단위 Minimum Reading	10 $\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Flat




JALB-71-RC	
유효피치 Stroke	$\pm 3.25\text{mm}$
눈금단위 Minimum Reading	10 $\mu\text{m}$
클램프 Clamp	있음(With)
단면형상 Edge Type	Round




JALB-71-FC	
유효피치 Stroke	$\pm 3.25\text{mm}$
눈금단위 Minimum Reading	10 $\mu\text{m}$
클램프 Clamp	있음(With)
단면형상 Edge Type	Flat



JALB-71-RS	
유효피치 Stroke	$\pm 3.25\text{mm}$
눈금단위 Minimum Reading	10 $\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Round




JALB-71-FS	
유효피치 Stroke	$\pm 3.25\text{mm}$
눈금단위 Minimum Reading	10 $\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Flat




# JALB-72




JALB-72-R	
유효피치 Stroke	$\pm 6.5\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Round




JALB-72-F	
유효피치 Stroke	$\pm 6.5\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Flat



JALB-72-RC	
유효피치 Stroke	$\pm 6.5\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	있음(With)
단면형상 Edge Type	Round



JALB-72-FC	
유효피치 Stroke	$\pm 6.5\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	있음(With)
단면형상 Edge Type	Flat





# JALB- 73 / 74




JALB-73-RS	
유효피치 Stroke	$\pm 12.5\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Round



JALB-73-FS	
유효피치 Stroke	$\pm 12.5\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Flat



JALB-74-F	
유효피치 Stroke	$\pm 25\text{mm}$
눈금단위 Minimum Reading	$10\mu\text{m}$
클램프 Clamp	없음(Without)
단면형상 Edge Type	Flat



# JALB 73 - DIG

JALB-73-F-DIG	
유효피치 Stroke	±12.5mm
최소단위 Minimum Reading	10μm
클램프 Clamp	없음(Without)
단면형상 Edge Type	Flat

